



US 20250074644A1

(19) **United States**

(12) **Patent Application Publication**
LANGEN

(10) **Pub. No.: US 2025/0074644 A1**

(43) **Pub. Date: Mar. 6, 2025**

(54) **METHOD AND SYSTEM FOR ORDER FULFILMENT**

B65H 3/08 (2006.01)

G05B 15/02 (2006.01)

G05B 19/418 (2006.01)

(71) Applicant: **H. J. Paul LANGEN**, Brampton (CA)

G06Q 10/08 (2006.01)

(72) Inventor: **H. J. Paul LANGEN**, Brampton (CA)

G06Q 10/087 (2006.01)

G06Q 30/0601 (2006.01)

(21) Appl. No.: **18/951,047**

(52) **U.S. Cl.**

(22) Filed: **Nov. 18, 2024**

CPC *B65B 43/145* (2013.01); *B65B 43/265*

(2013.01); *B65B 43/305* (2013.01); *B65B*

61/26 (2013.01); *B65G 57/22* (2013.01);

B65H 3/0808 (2013.01); *G05B 15/02*

(2013.01); *G05B 19/418* (2013.01); *G05B*

19/41865 (2013.01); *G06Q 10/08* (2013.01);

G06Q 10/087 (2013.01); *G06Q 30/0635*

(2013.01)

Related U.S. Application Data

(63) Continuation of application No. 17/469,557, filed on Sep. 8, 2021, now Pat. No. 12,172,787, which is a continuation of application No. 16/444,673, filed on Jun. 18, 2019, now Pat. No. 11,136,153, which is a continuation of application No. 16/230,979, filed on Dec. 21, 2018, now Pat. No. 10,556,713, which is a continuation of application No. 14/644,842, filed on Mar. 11, 2015, now abandoned.

(60) Provisional application No. 61/951,263, filed on Mar. 11, 2014.

(57)

ABSTRACT

A method of fulfilling an order comprising at least one product is provided. The method includes receiving an order comprising at least one product, determining a suitable case from a plurality of available cases for holding the at least one product, said determining being a function of one or more characteristics of each product of the at least one product and one or more characteristics of the plurality of available cases; forwarding information identifying the suitable case to a case former; providing a case blank corresponding to said suitable case to said case former; erecting a suitable case from said case blank corresponding to said suitable case with said case former; and prior to the loading said suitable case with said at least one product, labelling said suitable case with at least one label.

Publication Classification

(51) **Int. Cl.**

B65B 43/14 (2006.01)

B65B 43/26 (2006.01)

B65B 43/30 (2006.01)

B65B 61/26 (2006.01)

B65G 57/22 (2006.01)

| | |
|---|---|
| From: Vendor Name Shipping Address City, State, Zip | To: Customer Name 123 Main St. New York, NY 10001 |
| Ship to Postal Code 10001 | Carrier: Logistics, INC |
| PO: 985290 Qty: 15 | |
| Store Number: 298 | For: Location: 298 123 Main St. New York, NY 10001 |
| Serial Shipping Container 8347882 4890 438979 167 2 | |

1283A




FIG. 1A




FIG. 1B




FIG. 2





FIG. 3

FIG. 4






FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D








FIG. 9








FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 19




FIG. 22




FIG. 23




FIG. 25




FIG. 26




FIG. 26A




FIG. 27





FIG. 28






FIG. 32




FIG. 33





FIG. 34A

FIG. 34B




FIG. 35A




FIG. 35B




FIG. 35C




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43





FIG. 44

FIG. 45






FIG. 46




FIG. 47




FIG. 48




FIG. 49



FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 54A




FIG. 55




FIG. 56




FIG. 57







FIG. 58

| | |
|---|--|
| From: Vendor Name Shipping Address City, State, Zip | To: Customer Name 123 Main St. New York, NY 10001 |
| Ship to Postal Code 10001  | Carrier: Logistics, INC |
| PO: 985290 Qty: 15 | |
| Store Number: 298  | For: Location: 298 123 Main St. New York, NY 10001 |
| Serial Shipping Container 8347882 4890 438979 167 2  | |

1283A

FIG. 59

| | | |
|---|---|---|
| From: Origin ID: #### Paul Reinhener 584 Elm Street Nashville, TN 18417 | FedEx  | Ship Code: #### Account: S***** |
| Ship To: 412356-450 Bill Sender Chris Shiflett 37 East 14th St. New York, NY 10011 | | REF: Order 6541365  Delivery Address Bar Code |
|  | Priority Overnight | TUE Deliver By: 14 FEB 06 |
| | TRK# 4700 3402 8719 10011 NY-US | XA KLLA  |

1283B

FIG. 60




FIG. 61

Customer Order Fulfillment System




FIG. 62A

Customer Order Fulfillment System




FIG. 62B

METHOD AND SYSTEM FOR ORDER FULFILMENT

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 17/469,557 filed on Sep. 8, 2021, which is a continuation of U.S. patent application Ser. No. 16/444,673 filed on Jun. 18, 2019 (now U.S. Pat. No. 11,136,153 issued on Oct. 5, 2021), which is a continuation of U.S. patent application Ser. No. 16/230,979 filed on Dec. 21, 2018 (now U.S. Pat. No. 10,556,713 issued on Feb. 11, 2020), which is a continuation of U.S. patent application Ser. No. 14/644,842 filed on Mar. 11, 2015, which claims priority from U.S. Provisional Patent Application No. 61/951,263 filed on Mar. 11, 2014. The contents of the aforementioned applications are incorporated by reference herein.

[0002] This application also incorporates by reference herein International PCT Patent Application Serial No. PCT/CA2013/000245 filed on Mar. 15, 2013 and U.S. Provisional Patent Application Ser. No. 61/637,665 filed on Apr. 24, 2012, in their entireties.

FIELD OF THE INVENTION

[0003] The present invention relates generally to methods and systems for order fulfilment such as order fulfilment of products ordered by customers. It also relates to systems and methods for erecting cases from case blanks.

BACKGROUND

[0004] Containers are used to package many different kinds of products. One form of container used in the packaging industry is what is known generically as a “box” and it can be used to hold various products and sometimes other boxes containing products. Some in the packaging industry refer to boxes used to package one or more products as “cartons”. Also in the industry there are containers/boxes that are known by some as “cases”. In this patent document, including the claims, the words “case”, “cases”, “carton”, “cartons” “container” and “containers” are used interchangeably to refer to boxes, cartons, trays and/or cases and the like that can be used to package any type of items including products and other cartons.

[0005] Cases come in many different configurations and are made from a wide variety of materials. However, many cases are foldable and are formed from a flattened state (commonly called a carton blank). Cases may be made from an assortment of foldable materials, including but not limited to cardboard, chipboard, paperboard, corrugated fibreboard, other types of corrugated materials, plastic materials, composite materials, and the like and possibly even combinations thereof.

[0006] Cases can be used to fulfil an order initiated by a customer for one or more products by obtaining each product from one or more locations in a storage facility such as a warehouse, loading the product(s) into a case, sealing the case, and then shipping the loaded case to a customer.

[0007] However, there are many obstacles to providing efficient methods and systems to fulfil customer orders, particularly where it is desirable to be able to fulfil orders for a large number of customers that may each have orders for a wide range of different kinds and/or number of products.

[0008] Accordingly, an improved method and system of product fulfilment is desirable.

SUMMARY

[0009] According to one aspect of the present invention there is provided a method of fulfilling an order, the order comprising at least one product, the method comprising: receiving an order comprising at least one product; determining a suitable case from a plurality of available cases for holding the at least one product, the determining being a function of one or more characteristics of each the product of the at least one product and one or more characteristics of the plurality of available cases; forwarding information identifying the suitable case to a case former; providing a case blank corresponding to the suitable case to the case former; erecting a suitable case from the case blank corresponding to the suitable case with the case former; and prior to loading the suitable case with the at least one product, labelling the suitable case.

[0010] According to another aspect of the present invention there is provided a method of fulfilling an order, the order comprising a plurality of products, the method comprising: receiving an order comprising a plurality of products; determining a plurality of suitable cases from the plurality of available cases for holding the plurality of products, the determining being a function of at least one characteristic of each the product of the plurality of products and of at least one characteristic of the plurality of available cases; forwarding information identifying the plurality of suitable cases to at least one carton former; providing case blanks corresponding to each of the plurality of suitable cases to the at least one case former; the at least one carton former erecting the plurality of suitable cases from the case blanks corresponding to each of the plurality of suitable cases with the one or more case formers; prior to loading each of the suitable cases formed from the case blanks with the one or more case formers, labelling each of the suitable cases.

[0011] According to another aspect of the present invention there is provided a system for fulfilling an order, the order comprising at least one product, the at least one product having a product characteristic, the system comprising: an order fulfilment processor; a first case blank magazine and a second case blank magazine, the first and second case blank magazines each holding at least one case blank, with the at least one case blank in the first magazine and the second magazine each having a case blank characteristic; a carton former operable to erect a case from a case blank held in either of the first and second case blank magazines; a case blank feeding apparatus operable to selectively feed a case from each of the first case blank magazines to the case former; a labelling device operable to label a case blank prior to loading the case with at least one product; wherein the order fulfilment processor is operable to (a) receive an order comprising at least one product; (b) determine a suitable case for the at least one product from the at least one case in the first and second case blank magazines as a function of the product characteristic of each the at least one product and the case blank characteristic of each the at least one case blank in the first and second case blank magazines; and (c) forward information identifying the suitable case to a case former; and wherein the case former is operable to: (i) receive the information identifying the suitable case from the order fulfilment processor: (ii)

select and receive a case blank from the case blank feeding apparatus for the suitable case from one of the first and second magazines; and (iii) erect the suitable case from the case blank; and wherein the labelling device is operable to label the case blank of the suitable case prior to or after the case former has erected the suitable case from the case blank.

[0012] According to another aspect of the present invention there is provided a system for fulfilling an order, the order comprising a plurality of products, the plurality of products each having a product characteristic, the system comprising: an order fulfilment processor; a plurality of case blank magazines each holding a plurality of available case blanks, with the plurality of available case blanks in each of the plurality of magazines having a case blank characteristic; a carton former operable to erect a case from a case blank of each of the plurality of case blank magazines; a case blank feeding apparatus operable to selectively feed a case blank from each of the plurality of case blank magazines to the case former; a labelling device operable to label each of the cases prior to loading each case with at least one product; wherein the order fulfilment processor is operable to (a) receive an order comprising a plurality of products; (b) determine at least one suitable case for holding the plurality of products as a function of the product characteristic of each of the case blank in the plurality of case blank magazines; and (c) forward information identifying a suitable case to a case former; and wherein the case former is operable to: (i) receive the information identifying a suitable case from the order fulfilment processor; (ii) select and receive a case blank from the case blank feeding apparatus corresponding to the suitable case from one of the available case blanks in one of the plurality of case blank magazines; and (iii) erect the suitable case from the case blank; and wherein the labelling device is operable to label the case blank of the suitable case prior to or after the case former has erected the suitable case from the case blank.

[0013] According to another aspect of the present invention there is provided a system for forming a container from a tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, wherein the plurality of panels comprise a first panel, and a second panel interconnected to the first panel, the second panel being rotatable relative to the first panel, the system comprising: (a) a plurality of magazines, each of the plurality of magazines for storing a plurality of tubular blanks in a generally flat configuration; (b) a case blank transfer apparatus for transferring a case blank from a selected one of the plurality of magazines to an erector head; (c) an erector head operable to received a case blank at a pick up location from the case blank transfer apparatus and open the case blank; (d) a folding and sealing apparatus; and (e) a movement sub-system having at least one movement apparatus connected to the erector head for moving the erector head along a cyclical path extending between the pick up location and the folding and sealing apparatus.

[0014] According to another aspect of the present invention there is provided a method for forming a container from a tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, wherein the plurality of panels comprise a first panel, and a second panel interconnected to the first panel, the second panel being rotatable relative to the first panel,

the method comprising: a. obtaining a selected case blank from one magazine of a plurality of magazines, each of the plurality of magazines storing a stack of tubular blanks in a generally flat configuration; b. transferring the selected case blank to an erector head; c. erecting the selected case blank with the erector head; and d. folding and sealing the selected case blank.

[0015] Other aspects and features of the present invention will become apparent to those of ordinary skill in the art upon review of the following description of specific embodiments of the invention in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] In the figures which illustrate by way of example only, embodiments of the present invention,

[0017] FIG. 1A is top right front perspective view of part of a carton forming system in accordance with an example embodiment of the present invention;

[0018] FIG. 1B is a schematic flow chart of the power and control sub-system of the part of the case forming system of FIG. 1A;

[0019] FIG. 2 is a top right rear perspective view of the carton forming system of FIG. 1A;

[0020] FIG. 3 is a top right side perspective view of the carton forming system of FIG. 1A;

[0021] FIG. 4 is a front schematic elevation view of the carton forming system of FIG. 1A, but with several components omitted;

[0022] FIG. 5 is a rear schematic elevation view of the carton forming system of FIG. 1A but with several components omitted;

[0023] FIG. 6A is a top right perspective view of a magazine sub-system;

[0024] FIG. 6B is a top right perspective view of the magazine sub-system of FIG. 6A, but with several components omitted;

[0025] FIG. 6C is a right side elevation view of the magazine sub-system of FIG. 6A, but with several components omitted;

[0026] FIG. 6D is a top plan view of the magazine sub-system of FIG. 6A;

[0027] FIG. 7 is a right side perspective view of the system of FIG. 1A but with several components omitted to show the blank intake system and the two erector heads and movement apparatuses, and a folding and sealing apparatus;

[0028] FIG. 8 is a top right rear perspective view of the components of FIG. 7;

[0029] FIG. 9 is a top right front perspective view of the components of FIG. 7;

[0030] FIGS. 10A-10E are a plan, front and side elevation views and two perspective views, of a blank for a regular slotted case shown is a generally flattened tubular configuration;

[0031] FIGS. 11-16 are schematic right perspective sequential views of a blank of FIGS. 10A to 10E configured in an open configuration being sequentially processed into an erected carton;

[0032] FIGS. 17-25 and 27-29 are schematic right perspective views of system of FIG. 1A, but showing only a single movement apparatus, erector head and some parts of the folding and sealing apparatus, in various sequential stages of a blank of FIGS. 10A to 10E being processed into an erected carton;

[0033] FIG. 26 is a rear elevation view of the components of FIG. 17;

[0034] FIG. 26A is a schematic perspective view of part of the folding and sealing apparatus of system shown in FIG. 1A.

[0035] FIG. 30 shows a top right perspective view of a first embodiment of an erector

[0036] head;

[0037] FIG. 31 is a side elevation view of the erector head of FIG. 30;

[0038] FIG. 32 is a bottom right perspective view of the erector head of FIG. 30;

[0039] FIG. 33 is a bottom plan view of the erector head of FIG. 33;

[0040] FIG. 34A is a top right perspective view of a second embodiment of an erector head;

[0041] FIG. 34B is a right side elevation view of the erector head of FIG. 34A;

[0042] FIGS. 35A, 35B and 35C show the erector head of FIG. 34A in various stages of opening a blank;

[0043] FIGS. 36-44 show the erector head of FIG. 34A and a sealing apparatus in various stages of erecting a blank and assembling it into a carton;

[0044] FIG. 45 is a schematic perspective view showing an alternative embodiment of a carton forming system; and in particular alternate erector heads, their corresponding moving apparatus and folding apparatus.

[0045] FIG. 46 is a plan view of a blank for a tray that may be processed according to some embodiments of the system.

[0046] FIG. 47 is a perspective view of a blank for an over-wrapping regular slotted case (RSC) that may be processed according to some embodiments of the system.

[0047] FIG. 48 is a perspective view of a blank for an over-wrapping regular slotted case (RSC) that may be processed according to some embodiments of the system.

[0048] FIG. 49 is a perspective view of an HSC case that may be formed according to some embodiments of the system.

[0049] FIGS. 50-52 are perspective views of an alternate folding and sealing apparatus that may be used in some embodiments of the invention.

[0050] FIG. 53 is a plan view of case former that is an alternate embodiment to the carton/case forming system of FIGS. 1 to 44 with some components of the case magazines omitted for clarity

[0051] FIG. 54 is a rear right side perspective view of the case former of FIG. 53.

[0052] FIG. 54A is an enlarged view of portion 54A in FIG. 54 with additional components illustrated.

[0053] FIG. 55 is a rear left side perspective view of the case former of FIG. 53.

[0054] FIG. 56 is rear perspective view of the case former of FIG. 53.

[0055] FIG. 57 is a rear perspective view of part of the case former of FIG. 53.

[0056] FIG. 58 is a schematic diagram illustrating an order fulfilment system.

[0057] FIG. 59 is a sample label that may be generated and used in the system of FIG. 58.

[0058] FIG. 60 is another sample label that may be generated and used in the system of FIG. 58.

[0059] FIG. 61 is a sample of a case packing diagram that may be generated and used in the system of FIG. 28.

[0060] FIGS. 62A and 62B together form a schematic representation of the operation of a system of FIG. 58.

DETAILED DESCRIPTION

[0061] With reference initially to FIGS. 1A-3, an example of a carton/case forming system that may be used as part of a product order fulfilment system is a carton/case forming system 100 (generally referred to as carton forming system 100). Carton forming system 100 may include a frame generally referred to as frame 109. The frame 109 may have integrated with it a series of panels 103 that may be made from a plastic or glass and that may or may not be transparent or semi-transparent. One or more of the panels 103 may be configured to operate as a hinged door so that interior portions of system 100 can be accessed. System 100 may also include a magazine 110 adapted to receive, hold and move a plurality of carton blanks 111 while in a substantially flat orientation. System 100 may include at least first and second erector heads 120a, 120b for retrieving carton blanks from the magazine 110. Erector heads 120a, 120b may pick up the carton blanks 111 from the magazine 110 and then manipulate the blanks in such a way that, with the assistance of other components of system 100, the carton blanks 111 are transformed into erected cartons.

[0062] The erector heads 120a, 120b may be moved by a movement sub-system. The movement sub-system may include one or more movement apparatuses. For example, erector head 120a may be mounted to and moved by a first moving apparatus 115a. Second erector head 120b may be mounted to and moved by a second moving apparatus 115b. In some embodiments only a single erector head and movement apparatus may be provided, but this may result in a lower production rate of erected cartons compared to when particularly two or possibly more, movement apparatuses and erector heads are provided, as illustrated in the drawings.

[0063] System 100 may also include a folding and sealing apparatus generally designated 130, which may be configured to fold one or more flaps of each carton blank and provide for sealing of one or more flaps as part of the process in forming fully erected cartons. In co-operation with erector heads 120a, 120b, a common folding and sealing apparatus 130 may be configured to handle in alternating sequence, carton blanks 111 carried by both erector head 120a and erector head 120b. System 100 may also include a carton discharge conveyor 117 for receiving and moving away carton blanks 111 once they have been fully erected.

[0064] The structural/mechanical components of system 100 may be made from any suitable materials. For example, frame members, and many of the parts that make up the erector heads 120, moving apparatuses 115, many of the components and parts that make up folding and sealing apparatus 130, and magazine 110, may be made of steel or aluminium, or any other suitable materials. Aluminium is particularly suitable for most parts. However, plates that hold the suction cups on the erector head and flanges that mount on gearbox shafts can be made from stainless steel for strength and hardness. Parts and components may be attached together in conventional ways such as for example by bolts, screws, welding and the like.

[0065] An example of a scheme for the power and data/communication configuration for system 100 is illustrated in FIG. 1b. The operation of the components of carton forming system 100, and of system 100 as a whole, may be controlled

by a programmable logic controller (“PLC”) **132**. PLC **132** may be accessed by a human operator through a Human Machine Interface (HMI) module **133** secured to frame **109**. HMI module **133** may be in electronic communication with PLC **132**. PLC **132** may be any suitable PLC and may for example include a unit chosen from the Logix 5000 series devices made by Allen-Bradley/Rockwell Automation, such as the ControlLogix 5561 device. HMI module **132** may be a Panelview part number 2711P-T15C4DI module also made by Allen-Bradley/Rockwell Automation. It should be noted that not all of the sensors, motors, servo motors, drives, vacuums, vacuum generators and vacuum cups described hereinafter are specifically identified in FIG. 1B.

[0066] Electrical power can be supplied to PLC **132**/HMI **133**, and to all the various servo motors and DC motors that are described further herein. Compressed/pressurized air can also be supplied to the vacuum generators and pneumatic actuators through valve devices such as solenoid valves that are controlled by PLC **132**, all as described further herein. Servo motors may be connected to and in communication with servo drives that are in communication with and controlled by PLC **132**. Similarly, DC motors may be connected to DC motor drives that are in communication with and controlled by PLC **132**; again all as described further herein. Additionally, various other sensors are in communication with PLC **132** and may (although not shown) also be supplied with electrical power.

[0067] With reference now to FIG. 10A-10E and 11A, an example of one kind of tubular carton blank **111** that can be processed by system **100** to form a regular slotted case (RSC) is disclosed. Other kinds of carton blanks, tubular carton blanks, and tubular carton blanks of different sizes can be processed by system **100**.

[0068] Each carton blank **111** may be generally initially formed and provided in a flattened tubular configuration as shown in FIGS. 10A-10E. Each blank **111** has a height dimension “H”; a length dimension “L”; and a major panel length “Q” (see FIG. 10B). By inputting each of these three dimensions for a blank **111** to be processed by system **100**, into PLC **132**, PLC **132** can determine if the system **100** can process that size blank without the necessity for manual intervention to make an adjustment to one or more components of the system **100**. If PLC **132** determines that the adjustment can be made without human intervention, the PLC **132** may make the necessary adjustments to positions and/or movements of at least some of the components forming system **100**, including the path of movement of erector heads **120a**, **120b** as the erector heads move and cycle through their processing sequences.

[0069] However, in some systems **100**, for some size blanks **111**, PLC **132** may determine that human intervention of some kind is necessary to make set-up adjustments to the positioning/orientations of at least some of the components of the system to enable the system to process the blank and may accordingly inform an operator of system **100**.

[0070] Blank **111** may have opposed major panels A and C integrally interconnected to a pair of opposed minor panels B and D to form a generally cuboid shaped blank when opened. An overlap strip of carton blank material may be provided between panel B and panel A that can be sealed by conventional means such as a suitable adhesive, to provide an overlapping seam joint in the vicinity of “P” (see FIG. 10A). This overlap may join the panels A, B, C and D into a continuous blank that is of generally flattened tubular

configuration as shown in FIG. 10A. A number of such blanks **111**, in a flattened configuration, can be delivered to the vicinity of system **100** that can be erected into the generally open tubular configuration shown for example in FIG. 11.

[0071] Also, as shown in FIGS. 10A-10E and 11, are upper side major and minor flaps E, H, L, I that are provided one side of the respective major and minor panels A-D. A second set of major and minor flaps F, G, K and J are also provided on the opposite, lower/bottom sides of the major and minor panels A-D. However, in other embodiments, cartons having other side panel configurations can be formed. The panels and flaps can be connected to adjacent flaps and/or panels by predetermined fold/crease lines (shown in broken lines). These fold/crease lines may for example be formed by a weakened area of material and/or the formation of a crease with a crease forming apparatus. The effect of the fold lines is such that one panel such as for example panel A can be rotated relative to an adjacent panel such as D or B along the fold lines. Flaps may also fold and rotate about fold lines that connect them to their respective panels.

[0072] As shown in FIG. 11, blank **111** may be designated with a first datum line “W1” that passes through the mid-point of the fold line between panel D and flap K, and the mid-point of the fold line between panel B and flap J. This datum line W1 may be determined by PLC **132** for a particular blank or group of blanks **111** to be processed, based on the input of the dimensions H, L and Q of the blanks. Blank **111** may be designated with a second datum line “W2” that may be determined by PLC **132** and which passes along and is generally parallel to the fold line between panel D and flap K, and the mid-point of the fold line between panel A and flap F. Datum W1 will be parallel to Datum W2. PLC **132** may also determine the relative position of the bottom of the erected carton as this will be aligned with a vertical datum plane passing through Datum W1 and Datum W2. Aligning the position datum W2 and of the datum plane with other components in system **100** will ensure that the carton is properly positioned during processing through system **100**. Also, the vertical distance R between datum W1 and the datum line W2 may be calculated by PLC **132**. This can ensure that PLC **132** knows where it needs to position the erector head so that top panel A, and accordingly, datum W1 are properly positioned throughout the processing of the blank by system **100**.

[0073] System **100** is able to track and modify the position of the blank **111**, and in particular the vertical position of the datum line W1 of the blank as the blank moves longitudinally through system **100** and as various components of system **100** engage the blank **111** during its movements. This will ensure that the blank **111** being processed is appropriately positioned relative to the system components so that the system components engage the blank at the correct position on the blank during processing of the blank.

[0074] As will be described hereinafter, carton blank **111** may be transformed from a generally flattened tubular configuration to an open tubular configuration and the flaps may be folded and sealed to form the desired erected carton configuration. The carton may be configured as a top opening carton suitable to be delivered to a carton loading conveyor with an upwardly facing opening or with a side-wards facing opening suitable for side loading.

[0075] Carton blanks **111** may have flaps that provides material that can, in conjunction with a connection mechanism (such as for example with application of an adhesive, scaling tape or a mechanical connection such as is provided in so-called “Klick-lok™” carton blanks) interconnect flap surfaces, to join or otherwise interconnect, flaps to adjacent flaps (or in some embodiments flaps to panels), to hold the carton in its desired erected configuration.

[0076] Carton blanks **111** may be made of any suitable material(s) configured and adapted to permit the required folding/bending/displacement of the material to reach the desired configuration. Examples of suitable materials are chipboard, cardboard or creased corrugated fiber-board. It should be noted that the blank may be formed of a material which itself is rigid or semi-rigid, and not per se easily foldable but which is divided into separate panels and flaps separated by creases or hinge type mechanisms so that the carton can be erected and formed.

[0077] Turning now to the components of system **100**, various specific constructions of a suitable magazine **110** might be employed in system **100**. With particular reference now to FIG. 3, FIGS. 6a-d, and FIG. 7, magazine **110** may be configured to hold a plurality of carton blanks **111** in a vertically stacked, flattened configuration, and be operable to move the stack of carton blanks **111** longitudinally in a direction generally parallel to longitudinal axis Y under the control of PLC **132**, to a pick up position where an erector head **120a** and **120b** can retrieve cartons from the magazine.

[0078] Magazine **110** may comprise a single conveyor or other blank feed apparatus to deliver blanks to a pick up location. In the illustrated embodiment of FIGS. 1A to 9, two conveyors are disclosed: an in-feed conveyor **204**; and an alignment conveyor **206**. However, as will be described hereinafter in other embodiments, the blank feed apparatus may be configured with multiple in-feed conveyors feeding cartons/cases from multiple magazines that hold carton/case blanks having different configurations. This enables a system **100** to by automation, selectively and sequentially erect cartons that differ in size, type, and/or configuration from each other.

[0079] Returning to system **100** of FIGS. 1A to 9, in-feed conveyor **204** may be configured and operable to move a stack of blanks **111** from a stack input position (where a stack may be loaded onto conveyor **204** such as by human or robotic placement) to a position where the stack of blanks is transferred to horizontally and transversely aligned, alignment conveyor **206**. Alignment conveyor **206** may be positioned longitudinally downstream in relation to in-feed conveyor **204** and be used to move the stack of blanks to the pick up position. Magazine **110** may be loaded with, and initially hold, a large number of carton blanks **111** in a vertical stack, with the stack resting on in-feed conveyor **204**. A rear wall **212** mounted to a lower portion of a magazine frame generally designated **202**, can be configured to retain the one or more stacks from falling backwards when initially loaded on conveyor **204**. Rear wall **212** may have a generally planar, vertically and transversely oriented surface facing the stack of blanks **111**. Rear wall **212** and conveyor **204** may be of an appropriate length to be able to store a satisfactory number of stacks of blanks in series on conveyor **204**. PLC **132** can control the operation of conveyor **204** to move one stack at a time to the alignment conveyor **206**.

[0080] In feed-conveyor may have one or more stacks of blanks arranged longitudinally on a conveyor belt **214** so that they can in turn be fed onto alignment conveyor **206**. A sensor may be provided in the vicinity of conveyor **204** to monitor the number of stacks waiting on conveyor **204** and that sensor may be operable to send a warning signal to PLC **132** that can alert an operator that the magazine is low and needs to be replenished (e.g. because the stack on the alignment conveyor being processed by erector head **120** is the only one left). The sensor may be a part number 42GRP-9000-QD made by Allen Bradley.

[0081] Of particular note, a plurality of stacks of blanks might be provided on conveyor **204**. Each stack may be included with some kind of information indicator that can be read by an information reader such as electronic or an optical reading device. For example, a bar code may be provided on a stack of blanks such as on the top or bottom blank of the stack. The bar code may be read by a suitably positioned bar code reader. The bar code reader may be in communication with PLC **132**. The bar code may provide information indicative of a characteristic of the blanks in the stack. For example, the bar code may identify the size and/or type of blank in a particular stack. Other information indicators may be used such as for example RFID tags/chips and RFID readers. The information can then be automatically provided by the information reader to PLC **132** which can determine whether the current configuration of system **100** can handle the processing the particular type/size of blanks without having to make manual adjustments to any of the components. It is contemplated that within a certain range of types/sizes of blanks, system **100** may be able to handle the processing of different types/sizes of blanks without manual adjustment of any components of system **100**. The bar code/RFID tag may provide the information about the dimensions of the blank as discussed above and then PLC **132** can determine adjustments, if any that need to be made to (a) the erector device operation; (b) the magazine and the tampering apparatuses in the magazine; (c) to provide a suitable path for the movement of the movement sub-system to provide for suitable pick up of a blank from the magazine and suitable handling by the erector device and the folding and scaling apparatus; and (d) adjustment of at least some of the components of the folding and sealing apparatus to be able to process a particular blank or a particular stack of blanks. The result is that system **100** may be able to process automatically, at least some different types/sizes/configurations of blanks to form different cartons, without having to make manual operator adjustments to any components of system **100**.

[0082] Conveyor **204** may include a series of transversely and horizontally oriented rollers **210** mounted to the lower portion of a magazine frame **202** for free rotation. Rollers **210** may allow for generally horizontal longitudinal downstream movement of the stack towards conveyor **206**. A conveyor belt **214** may be provided that may be driven by a suitable motor such as a DC motor or a variable frequency drive motor **291** (see FIG. 1b). Motor **291** may be DC motor and may be controlled through a DC motor drive (all sold by Oriental under model AXH-5100-KC-30) by PLC **132**.

[0083] Conveyor belt **214** may have an upper belt portion supported on the rollers **210**. Once PLC **132** is given an instruction (such as by a human operator through HMI module **133**), upper belt portion of belt **214** may move longitudinally downstream towards conveyor **206**. In this

way belt **214** can move a stack of blanks **111** longitudinally downstream, with the stack of blanks at its outer transverse portions also being supported on the rollers **210**. PLC **132** can control motor **291** through the motor drive and thus conveyor **204** can be operated to move and transfer the stack towards and for transfer to the alignment conveyor **206**.

[**0084**] Stack alignment conveyor **206** may also include a series of transversely oriented rollers **208** that are mounted for free rotating movement to a lower portion of the magazine frame **202**. A conveyor belt **216** may be driven by a motor **292** that may be like motor **291** and with a corresponding motor drive. Motor **292** may also be controlled by PLC **132**. Belt **216** may be provided with an upper belt portion supported on rollers **208** and upon which the stack of blanks **111** may be supported. Conveyor belt **214** may be operated to move the stack of blanks **111** further longitudinally until the front face of the stack abuts with a generally planar, vertically and transversely oriented inward facing surface of front end wall **218**.

[**0085**] Conveyor belt **214** of conveyor **204** and conveyor belt **216** of conveyor **206** may be made from any suitable material such as for example Ropanyl.

[**0086**] A sensor **242**, such as an electronic eye model 42KL-D1LB-F4 made by ALLEN BRADLEY, may be located within the horizontal gap between belt **214** and belt **216**. Sensor **242** may be positioned and operable to detect the presence of the front edge of a stack of blanks as the stack of blanks begins to move over the gap between conveyor belt **214** and conveyor belt **216**. Upon detecting the front edge, sensor **242** may send a digital signal to PLC **132** (see FIG. **1b**) signalling that a stack has moved to a position where conveyor **206** can start to move. PLC **132** can then cause the motor **292** for conveyor **206** to be activated such that the top portion of belt **216** starts to move the stack downstream. In this way, there can be a “hand-off” of the stack of blanks from in-feed conveyor **204** to alignment conveyor **206**.

[**0087**] Once the rear edge of the stack of blanks **111** has passed the sensor **242** a signal may be sent to PLC **132** (see FIG. **1b**) which can then respond by sending a signal to shut down the motor **291** driving belt **214** of conveyor **204**. Conveyor **204** is then in a condition ready to be loaded with another stack of blanks **111**. Meanwhile conveyor **216** can continue to operate as it moves the stack of blanks **111** to the pick up position.

[**0088**] The presence of a stack of blanks **111** at the pick up location may be detected by a sensor **240** that may be the same type of sensor as sensor **242**. The sensor **240** may detect the presence of the front edge of a stack of blanks at the pick up position and may send a digital signal to PLC **132** signalling that a stack is at the pick up position. At the pick up position, the stack of blanks may be “squared up” and thereafter, once properly aligned, single carton blanks **111** may be retrieved in series from the stack of blanks **111** by the alternate engagement of the erector heads **120a**, **120b** with the upper most blank in the stack.

[**0089**] The magazine **110** may be configured and operable to enable the stack of blanks **111** to be properly positioned and oriented in a pick up position for proper engagement by one of the erector heads **120a**, **120b**. During movement of the stack of blanks **111** longitudinally by conveyors **204** and **206**, the left hand side of the stack of blanks may be supported and guided by a left hand side wall **200**. Side wall **200** may be mounted to a lower portion of lower frame **202**

and side wall **200** may be oriented generally vertically and may extend longitudinally for substantially the full lengths of conveyors **204** and **206**.

[**0090**] The right hand side of the magazine **110** adjacent conveyor **204** may be left generally open; however to the right hand side of conveyor **206** there may be a right hand side guide wall **201**.

[**0091**] Possible mounting arrangements for side walls **200** and **201** are illustrated in further detail in FIGS. **6A-6D**. In this regard, lower frame portion **202** may include bottom support plates **251**, **255**, **259** and **263** that are supported on the ground terrain/floor with these plates being spaced from each other and oriented in a generally transverse, parallel relationship to each other. Each of support plates **251**, **255**, **259** and **263** has mounted to an upper surface thereof, one of the tracks **253**, **257**, **261** and **265**. Side wall **200** may be supported by connector blocks **267** that fit onto and are capable of sliding laterally on and in relation to tracks **253** and **261**. Similarly side wall **201** may be supported by connector blocks **269** that fit onto and are capable of sliding laterally on and in relation to tracks **255** and **263**.

[**0092**] A drive mechanism may be provided to drive each of side walls **200** and **201** on their respective tracks. For side wall **200**, a drive mechanism that is in electronic communication with PLC **132** can be provided. By way of example, a servo motor **258** with gear head may be provided and be in electronic communication with PLC **132** through a servo drive (as per FIG. **1b**). Examples that could be used are servo motor MPL-B1530U-VJ42AA made by ALLEN BRADLEY, in combination with servo drive 2094-BC01-MP5-S also made by ALLEN BRADLEY and gear head AE050-010 FOR MPL-A1520 made by Apex.

[**0093**] A lead screw rod **262** may be inter-connected to servo motor/gear head **258**. Lead screw rod **262** may pass through a nut such as a brass nut **264**. Nut may be fixedly secured to a plate **293**. Plate **293** may be interconnected to spaced, generally vertically oriented bar members **294**. Bar members **294** may be interconnected to support frame (not shown) forming part of side wall **200**. By activating servo motor/gear head **258**, the rotation of the servo may rotate the screw rod **262**. As rod **262** passes through nut **264**, the nut is moved laterally either inwards or outwards, thereby causing wall **200** to slide on tracks **252**, **261** inwards or outwards depending upon the direction of rotation of screw rod **262**. An encoder may be provided within or in association with servo drive motor **258** and the encoder may rotate in relation to the rotation of the respective drive shaft of the servo drive. The encoder may be in communication with, and provide signals to the servo drive which can then pass on the information to PLC **132**. Thus, PLC **132** may be able to determine the longitudinal position of the screw rod **262** in real time and thus the transverse position of side wall **200** and can operate the servo drive **258** to adjust the position of the side wall **200**. The particular type of encoder that may be used is known as an “absolute” encoder. Thus once the encoder is calibrated so that a position of the screw rod **262** is “zeroed”, then even if power is lost to system **100**, the encoder can maintain its zero position calibration. However, as side wall **200** is not moved during processing of a blank **111**, the mechanism for adjusting the transverse position of side wall **200** may alternatively be a simple hand crank mechanism instead of a servo drive motor in communication with PLC **132**. It should be noted that a proper position for left side wall **200** during the processing of a blank stack is

that shown in FIG. 7, with the wall 200 in abutment with the left side edges of the blanks in each stack. The proper positioning of wall 200 will ensure that the datum line W1 when the blanks are flattened is properly transversely aligned to be picked up by erector heads 120a, 120b and moved through folding and sealing apparatus 130, as described hereinafter in detail to achieve proper folding and scaling of the carton blank.

[0094] Similarly, for side wall 201, a drive mechanism 260 (that may be the same types of components that used for side wall 200) that is also in electronic communication with PLC 132 may be provided. By way of example, a servo motor with gear head designated 260 may be provided and also be in electronic communication through a servo drive with PLC 132. A lead screw rod 266 may be inter-connected to servo motor/gear head 266 (which may be like servo/gear head 268). Lead screw rod 266 may pass through a nut such as a brass nut (not visible in Figures) like nut 264. The nut may be fixedly secured to a plate 295. Plate 295 may be inter-connected to spaced, generally vertically oriented bar members 296. Bar members 296 may be interconnected to side wall support frame generally designated 271 (see FIG. 6c) that forms part of side wall 201. By activating servo motor/gear head 260, the rotation of the servo may rotate the screw rod 266. As rod 266 passes through the nut, the nut is moved laterally either inwards or outwards, thereby causing wall 201 to slide on tracks 257, 265. An encoder may be provided within or in association with servo drive motor 260 and the encoder may rotate in relation to the rotation of the respective drive shaft of the servo motor. The encoder may be in communication with a servo drive and thus provide signals to PLC 132. Thus, PLC 132 may be able in real time to determine the longitudinal position of the screw rod 266 and thus the transverse position of side wall 201. Thus PLC 132 can operate the servo motor 260 to adjust the position of the side wall 201. An “absolute” encoder may also be used in this application.

[0095] During operation of system 100 in erecting a carton, side wall 200 may remain stationary, but side wall 201 may be moved laterally as part of the blank stack alignment procedure to provide for generally longitudinal alignment of the side edges of blanks 111 in the stack as they are held between side walls 200 and 201.

[0096] A lateral tampering apparatus may be secured to side wall 201 and may be used to affect lateral alignment of the front and rear side edges of the blanks 111 in the stack (i.e. the front and rear edges of the blanks in the stack are generally aligned with a vertical axis such as axis Z in FIG. 7). A lateral tampering apparatus generally designated 275 may include a horizontally and longitudinally oriented support plate 270 that may be attached at either end to vertical members of side wall support frame 271. Attached to an outer surface of plate 270 may be a track 272. Secured to track 272 for sliding longitudinal movement along track 272 may be a slider block 273. Attached to slider block 273 may be a pair of upstanding support plates which at their upper ends are secured to a double acting, pneumatic actuator 276 such as the model DFM-25-80-P-A-KF Part #170927 made by Festo. Actuator 276 may have one or more piston arms (not visible in FIG. 6b or 6c because they are shown retracted). Piston arms of actuator 276 may reciprocate between retracted and extended positions—back and forwards in a longitudinal direction. With reference to FIG. 1b, a pneumatic actuator may be supplied with pressurized air

communicated through electronic solenoid valves for causing the piston arms to retract and extend. The solenoid valves may be a model CPE14-M1Bh-5J-1/8 made by Festo and may be controlled by PLC 132. Alternatively, a linear servo drive system—similar to one described in connection with the movement of side walls 200 and 201—may be provided for this actuator. Such a servo drive system could be controlled by PLC 132. PLC 132 could make adjustments to the movement of both side walls 200 and 201 as well as this actuator for the lateral tampering apparatus, such that magazine 110 could be automatically adjusted to process a wide range of sizes of blanks.

[0097] It should be noted that during the operation of system 100 in erecting cartons, the slider block 273 will not move along track 272. Slider block 273, and the components attached directly or indirectly thereto including actuator 276, will not move longitudinally during operation. However the longitudinal position of slider block 273 can be adjusted during the set-up of system 100 when processing particular sizes of carton blanks.

[0098] Attached to the end of the piston arms of actuator 276 may be a transverse plate 278 that may pass through a longitudinally extending slot 279 through side wall 201. The distal end of plate 278 from piston arms is attached to a vertical tamper plate 280 that is positioned transversely inwards from the inner surface of side wall 201. Retraction of the piston arms of actuator 276 can cause plate 278 to engage the rear side edges of the blanks 111 in the stack and as the front edges of those blanks are pushed up against the inner surface of the front wall 218, the front and rear edges of the blanks can be laterally aligned. While a pneumatic actuator 276 is illustrated, other alignment devices could be used. For example, a linear servo drive in communication with PLC 132 might be employed, that would perform the same function but it could electronically position the vertical tampering plate 280, and the operator may not have to adjust it manually during system set up.

[0099] By operation of PLC 132, suitable adjustment of right side wall 201 and tamper plate 280, the blanks 111 can be moved to precisely the known pick up location and their orientation may be “squared-up” blanks 111 in a stack of blanks that is held against front wall 218, and may thus ensure that the blanks 111 are in the proper location for being engaged by the erector heads 120a, 120b.

[0100] In particular, once the stack of blanks 111 have generally reached the pick up location, PLC 132 can send a signal to drive mechanism 260 to cause the drive mechanism 260 to cause side wall 201 to move laterally inwards towards the side of stack of blanks 111. PLC 132 will cause the drive mechanism 260 to move a sufficient distance to cause the edges of the blanks 111 to become in contact along their length with inner surface of longitudinally aligned inner surface of side wall 201. However, PLC 132 will not cause side wall 201 to be moved to such an extent that it creates a force on the stack of blanks such that causes the blanks to buckle/be damaged if they are compressed to a significant extent between side walls 200 and 201. PLC 132 may be able to determine how much to move side wall 201 towards side wall 200 by virtue of the carton size dimensions that have been inputted into the PLC, including dimension H (see FIG. 10A). The amount of slight compression can be fine tuned such as by trial and error for different sized carton. It should be noted that for many sized cartons, the manufacturers comply with industry standard carton sizes.

[0101] Once the longitudinal alignment has been completed by side wall 201, PLC 132 can cause actuator 276 to be activated to cause the vertical plate 280 to engage the rear edges of the blanks 111 in the stack. PLC 132 may cause the drive mechanism 260 to move a sufficient distance to cause the rear edges of the blanks 111 to come in contact along their length with inner surface of laterally aligned inner surface of plate 280. However, the amount of retraction of the piston arms will not cause side wall vertical plate 280 to be moved to such an extent that it creates a force on the stack of blanks that would cause the blanks to buckle/be damaged if they are compressed too much between plate 280 and front wall 218. The appropriate manual positioning and securement (such as by tightening screws appropriately positioned through block 273, can secure actuator 276 at an appropriate longitudinal position on rail 270.

[0102] Thus, by way of review: The tampering actuator 276 may ride on the side guide wall 200. For a carton of a particular size/shape, the tampering actuator 276 can be adjusted manually in a fore-aft direction so that when the actuator 276 is retracted, the vertical tamper bar 280 is in the right position to push the blanks up against the front wall 218 (without squeezing them).

[0103] The sliding assembly of components that includes actuator 276 may also have a pointer or indicator, and on the stationary part of the magazine there may be a numeric scale to assist in rapidly manually adjusting the actuator to the correct position on rail 270 for a known case size.

[0104] In review the tampering sequence for ensuring the blanks are properly squared up at the pick up location steps include the following:

[0105] 1. The right-hand-side magazine side guide wall 201 under control of PLC 132 expands wide enough to allow the stack of blanks to enter on alignment conveyor 206, even if the stack is misaligned and/or the blanks in the stack are not perfectly square with each other and in relation to the X-Y axes.

[0106] 2. The belt 216 advances the stack of blanks 111 towards the front stop datum and may abut with front wall 218

[0107] 3. The tampering actuator 276 is extended, and then the side guide wall 201 may contract to make contact with the side of the case stack and press the side wall 201 against the left hand side guide wall 200. This aligns the cases so the side edges of blanks are aligned with each other and the longitudinal side wall of the walls 200 and 201.

[0108] 4. The tampering actuator 276 may retract, and the tampering bar 280 presses the stack forward, thereby aligning the blanks in the stack so that their front and rear edges are vertically aligned with each other and with the inner face of the bar 280 and the inside surface of front wall 218

[0109] 5. The blanks are then properly positioned so that the erector heads can begin picking up blanks from the stack.

[0110] Turning now to other components of system 100, to retrieve blanks from the magazine 110, at least a first engagement device may be provided to engage a panel of a blank 111 and thus be able to hold and move the blank. Where the blank is a tubular blank, system 100 may be provided with a first engagement device for engaging one panel (e.g. Panel A) of a blank and a second engagement device for engaging a second panel (e.g. Panel B) of the

blank. 111. The first and second engagement devices may comprise one or more suction cups providing a suction force onto a panel acting generally normal to the surface of the panel that is engaged, as described further below. Other types of suitable engagement devices might be employed. The first and second engagement devices may be rotatable relative to each other so that the first panel can be rotated relative to the second panel. The first and second engagement devices may be mounted to a single common erector head.

[0111] With reference to FIG. 7, system 100 may be provided with a movement sub-system that may be a pair of movement apparatuses each supporting and moving one of erector heads 120a, 120b. Each erector head 120a, 120b may have a dedicated, independently driven and controlled movement apparatus 115a, 115b. Thus erector head 120a may be supported and moved by movement apparatus 115a. Similarly erector head 120b may be supported and moved by movement apparatus 115b. Movement apparatus 115a may be constructed in a manner that is substantially identical to movement apparatus 115b but may be configured as mirror image of movement apparatus 115b. In this way, movement apparatus 115a may support erector head 120a from a right hand side and movement apparatus 115b may support erector head 120b from a left hand side, in such a manner that the erector heads 120a, 120b may both be moved along the same longitudinal and vertical path. The common path of erector heads 120a, 120b, may be a cyclical path that lies substantially in or is parallel to a plane that it parallel both vertical axis Z and longitudinal axis Y in FIG. 7. Thus movement of the erector heads 120a, 120b may only be in vertical Z and longitudinal Y directions (i.e. directions parallel to axes Z and Y in FIG. 7), and there may be no substantial movement in a lateral Z direction (i.e. a direction parallel to axis X in FIG. 7). If the movement of the erector heads 120a, 120b is restricted to only Z and Y directions, a moving apparatus for each can be constructed that is relatively less complex than if movement in all three directions is required.

[0112] The movement of heads 120a, 120b by movement apparatuses 115a, 115b respectively, may be synchronized such that they may travel along the same longitudinal and vertical path but they move out of phase with each other so that one erector head does not interfere with the other erector head, as will be described further below. Thus, the relative positions of the two erector heads 120a, 120b can be arranged so that the heads they do not collide or otherwise interfere with each other during operation of system 100.

[0113] Only the detailed construction of left side movement apparatus 115b will be described herein, it being understood that movement apparatus 115a may be constructed in a substantially identical manner as a mirror image of moving apparatus 115b. With particular reference to FIGS. 4, 5, 7, 8, 9 and 17, movement apparatus 115b may include a vertical movement device and a horizontal movement device. The vertical movement device may include a generally hollow vertically oriented support tube 169 that may be generally rectangular in cross section. Support tube 169 may be formed from a unitary tubular piece of material or may be formed into opposed, vertically extending and oriented, surfaces 164, 165, 166 and 168 that may be inter-connected together using conventional mechanisms such as bolts, welding etc. Support tube 169 may be secured to a horizontally extending brace plate 182. Brace plate 182

may be interconnected to a vertically extending brace plate **180**. The bottom portion of brace plate **180** may be interconnected by way of a series of angled plates generally referred to as **183**, to the lower end of support tube **169**.

[0114] At the upper end of support tube **169** may be mounted a freely rotatable pulley wheel **155b**. At the bottom end of plates **164**, **166**, erector head **120b** may be fixedly attached to support tube **169** by means of a horizontally extending mounting plate that is connected to support tube **169**, which engages with a pair of spaced mounting block **190a**, **190b** that may be joined with bolts through bolt holes **191a**, **191b** in blocks **190a**, **190b** that also pass through the mounting plate at the bottom of support tube **169**. Thus, as erector head **120b** is interconnected to support tube **169**, erector head **120b** will move in space with support tube **169**.

[0115] To support the support tube **169** and erector head **120b** that is connected thereto, and facilitate movement of the support tube **169** and erector head **120b** in horizontal motion, a horizontal movement device may be provided and may include a slide block **158** that may use a rail system to move horizontally and may be provided with a pair of spaced, longitudinally and horizontally extending short inner blocks, each one fitting on one longitudinally extending rail **160**, **162** that holds the blocks securely but allows blocks to slide horizontally relative to the rails. An example of a suitable rails system is the Bosch Rexroth ball rail system in which the rails are made from steel and the blocks have a race of ceramic balls inside allowing the block to slide on the rails. Rails **160**, **162** are generally oriented horizontally and may be attached to the frame **109**. Slide block **158** may be mounted to rails **160** or **162** for horizontal sliding movement along the rails. Secured to the front face of slider block **158** are four freely rotatable pulley wheels **155a**, **155c**, **155d** and **155f** which have drive belt **153** pass around them as described below. Slide block **158** may also use a rail system to allow support tube **169** to be connected to it and also move vertically relative to slide block **158**. Accordingly, extending vertically along a back surface of tube **169** may be a vertically and longitudinally extending rail. Support block may have a runner block interconnected to the vertical rail on support tube **169**. Thus support tube **169** can slide horizontally relative to slide block **158**. Again, a suitable rail system is the Bosch Rexroth ball rail system referenced above.

[0116] A drive apparatus may also be provided to drive the horizontal movement device and the vertical movement device. For example, the drive apparatus may include a pair of drive motors interconnected to a drive belt, with the drive belt being inter-connected to the horizontal and vertical movement devices. For example, the drive apparatus may include a left belt drive motor **150** (which may be a servo motor such as the model MPL-B330P-MJ24AA made by Allen Bradley) may be mounted to a longitudinally extending beam member **108** that is connected to frame **109** (see FIGS. 1a, 2 and 3). Servo drive **150** may have a drive wheel **152**. Similarly, a right belt drive **154** (which may be a servo motor like servo drive **150**) may also be mounted to beam member **108** connected to frame **109**. Servo drive **154** may have a drive wheel **156**. Servo motor **152** may be longitudinally spaced from, and may be horizontally aligned with, servo motor **154**. Both servo motors **150** and **154** can be driven in both directions at varying speeds, such rotation being controllable through servo drives by PLC **132** (see FIG. 1b). Both servo motors **150** and **154** may be provided

with two separate ports **364a**, **364b**. One for the ports may be for supplying a power line and the other for a communication line to facilitate the communication with the servo drive and PLC **132**. It should be noted that all of the servo motors described in this document may be similarly equipped. Servo motors **150**, **154** may also have a third input which may provide input for an electric braking mechanism.

[0117] Apparatus **115a** may also include a continuous drive belt **153** that may for example be made from urethane with steel wires running through it. Belt **153** may be engaged and may be driven by motors **150** and **154** under control of PLC **132** as it may independently control through their respective servo drives, the operation of both servo motor **152** and servo motor **154**. Belt **153** extends continuously from a start location at the bottom left side of support tube **169**, where belt is fixedly attached to a belt block **159a** that is attached to support tube **169**. From there belt extends upwardly on a first portion **153g** to block pulley **155f**; around the upper side of block pulley **155f**; From block pulley **155f**; belt **153** extends horizontally along a second portion **153h** to servo drive wheel **152**. The belt then passes around and is engaged by servo drive wheel **152**, on a third portion **153a** on the underside of pulley **155a**, upwards along a fourth portion **153b** to pulley **155b**. From there belt extends around pulley **155b**, downwards on a fifth portion **153c** to block pulley **155c**, around block pulley **155c** along a sixth portion **153d** to servo drive wheel **156**. After passing around and being engaged by servo drive wheel **156**, belt **153** extends continuously from around servo drive wheel **156**, on to a seventh portion **153e** to the upper side of block pulley **155d**. From block pulley **155d**, belt **153** then extends vertically downwards along an eighth portion **153f** to belt block **159b** where the belt terminates. Belt **153** vertically supports the support tube **169** both at the bottom as it is interconnected to support tube **169** with blocks **159a**, **159b**, and at the top of support tube **169** where it passes **155b**. Thus belt **153** is indirectly also vertically supporting erector head **120b**. Furthermore, by adjusting the relative rotations of servo drive wheels **152** and **156**, the relative lengths of all belt portions can be adjusted through the operation of the servo motors **150** and **154**. Thus, the relative vertical position of support tube **169** relative to slide block **158** can be adjusted. Additionally, by adjusting the relative rotations of servo drive wheels **152** and **156**, through the operation of the servo motors **150** and **154** the horizontal position of slide block **158** on rails **160**, **162** can be adjusted thus altering the horizontal position of support tube **169** and erector head **120b**. It will thus be appreciated that by adjusting the direction and speeds of rotation of drive wheels **152**, **156** relative to each other the support tube **169** can be moved vertically and/or horizontally in space within the physical constraints imposed by among other things the position of the servo drive wheels **152** and **156**, the length of the belt **153**, and the length of support tube **169**. The following will be appreciated with reference to FIG. 17 in particular:

[0118] If wheels **152** and **156** both remain stationary then the position of support tube **169** will not be altered;

[0119] If wheels **152** and **156** both rotate in the same clockwise direction and at the same speed relative to each other, then support tube **169** (and thus erector head **120b**) will move horizontally from right to left;

[0120] If wheels **152** and **156** both rotate in the same counter-clockwise direction and at the same speed

relative to each other, then support tube **169** (and thus erector head **120b**) will move horizontally from left to right;

[0121] If wheel **152** rotates counter-clockwise, and wheel **156** rotates in opposite clockwise rotational directions, but both wheels rotate at the same rotational speed relative to each other, then support tube **169** (and thus erector head **120b**) will move straight vertically downward;

[0122] If wheel **152** rotates clockwise, and wheel **156** rotates in opposite counter-clockwise rotational directions, but both wheels rotate at the same rotational speed relative to each other, then plates **164**, **166** will move straight vertically upwards.

[0123] It will be appreciated that if the speeds and directions of the two servo motors are varied in different manner, then the motion of the support tube **169** (and thus erector head **120b**) can be created that has both vertical upwards or downwards component as well as a horizontally right to left, or left to right movement. Thus any desired path within these two degrees of freedom (vertical and horizontal) can be created for support tube **169** (such as a path having curved path portions) (and thus erector head **120b**). Thus by controlling the rotational direction and speed of the motors **150**, **154** independently of each other, PLC **132** can cause support tube **169** (and thus erector head **120b**) to move along any path, within the physical constraints imposed by the spacing of the drive wheels **152**, **156** and pulley wheel **155b**, and the bottom of support tube **169** in vertical and horizontal directions to allow for the end erector **120b** to carry a carton blank **111** through the various processing steps performed by system **100**.

[0124] It will also be appreciated that by providing two opposed moving apparatuses **115a**, **115b**, the movements of each of the end effectors **120** can be co-ordinated and synchronized so that even though they move along the same path, the movement of the end effectors are out of phase (for example by 180 degrees).

[0125] Thus the movements of one end effector will not interfere with the movement of the other. An encoder may be provided for each of the servo drive motors **150** and **154** and the encoders may rotate in relation to the rotation of the respective drive wheels **152**, **156**. The encoders may be in communication with, and provide signals through the servo drives to PLC **132**. Thus PLC **132** can in real time know/determine/monitor the position of the belt **153** in space and thus will determine and know the position of the erector head **120b** in space at any given time. The particular types of encoders that may be used are known as "absolute" encoders. Thus the system can be zeroed such that due to the calibration of both encoders of both servo drives **150** and **154**, the zero-zero position of the erector head in both Z and Y directions is set within PLC **132**. The zero-zero position can be set with the erector head at its most horizontally left and vertically raised position. PLC **132** can then substantially in real time, keep track of the position of the erector head **120b** as it moves through the processing sequence for a blank **111**.

[0126] PLC **132** and the encoders associated with the servo motors **150**, **154** and their servo drives on each of apparatuses **115a**, **115b** may be capable of being able to be set at zero-zero positions for each of the two separate erector heads **120a**, **120b**. PLC **132** can then substantially in real time, keep track of the position of both the erector heads

120a, **120b** as they both independently move through the processing sequence for a blank **111**.

[0127] Also associated with moving apparatus **115b** is a first, generally horizontally oriented caterpillar device **114** having an input end **114a** and an output end **114b**. A second, generally vertically oriented caterpillar device **118** is also provided and has an input end **118a**, and an output end **118b**. Caterpillars **114** and **118** may have a hollow cavity extending along their length. Within the cavities of caterpillars **114**, **118** hoses/wires carrying pressurized air/vacuum and electrical/communication wires can be housed. Caterpillar **114** allows such hoses and wires to move longitudinally as the support tube **169** and erector head **120b** are moved longitudinally. Caterpillar **118** allows such hoses and wires to move vertically as the support tube **169** and erector head **120b** are moved vertically. The hoses and wires may extend from external sources to enter at an inlet **114a** of caterpillar **114** and emerge at an outlet **114b**. Once leaving outlet **114b**, the hoses and wires may extend to enter at an inlet **118a** of caterpillar **118** and emerge at an outlet **118b**. These hoses and wires may then pass from outlet **118b** into the input hoses **190** and **191** on erector head **120b** (see FIG. **30**). In this way both pressurized air/vacuum and/or electrical communication wires may be brought from locations external to the frame **109** onto the moving erector head **120b**. An example of suitable caterpillar devices that could be employed is the E-Chain Cable Carrier System model #240-03-055-0 made by Ignus Inc. It should be noted that electrical communication between the PLC **132** and the erector head **120b** could in other embodiments be accomplished using wireless technologies that are commercially available.

[0128] Turning now to FIGS. **30** to **33**, left hand side erector head **120b** is shown in isolation. Right hand side erector head **120a** may be constructed in the same manner as erector head **120b**, but may be supported from the right hand side moving apparatus **115a**, in contrast to erector head **120b** which may be supported from the left hand side by left hand moving apparatus **115b**.

[0129] Erector head **120b** may have a body generally designated as **300** that may comprise of a number of components. Many of the components of erector head **120b** may be made from a strong material such as a metal (e.g. aluminium, steel, etc.), a hard and strong plastic such as or other suitable materials including composite materials.

[0130] Erector head **120b** may be generally configured to handle a range of sizes of carton blanks **111** that can be formed into a carton. Erector head may be configured by providing easy attachment to support tube **169** using mounting blocks **190a**, **190b** and bolts etc. to permit for the easy interchange of erector heads **120** so that the system can in some circumstances, be readily adapted to forming differently sized/shaped cartons from differently configured blanks.

[0131] In one embodiment, erector head **120b** may include a rotatable paddle **310** connected to a distal end portion **314a** of a paddle arm **314**. Paddle arm **314** may have an end portion **314b** opposite to distal end portion **314a**, that is formed with a circular opening that facilitates arm **314** being connected to a shaft **316**. Paddle **310** can rotate with shaft **316** about the longitudinal axis of shaft **316**. Shaft **316** may be connected to a rotary actuator **399** such as a double acting rotary pneumatic actuator manufactured by Festo under engineering part #DSM-32-270-CC-FW-A-B. Actuator **399** can cause rotation of shaft **316** clockwise and counter-

clockwise around its axis of up to 270 degrees. Rotary actuator **399** may be supplied with pressurized air supplied by hoses (not shown) connected to ports **395** and **397**. Those hoses may also be connected to a solenoid valve device **340** which may be controlled by PLC **132**. In this way the rotation clockwise and counter-clockwise of paddle **310** may be controlled by PLC **132**.

[0132] Also formed as part of body **300** of erector head **120b** is a bottom suction plate **327** that is generally shaped in a square cross configuration to provide flanged openings for such cups. In each of the open flanges of plate **327** is positioned a suction cup **312**. It should be noted that while many types of suction cups may be employed on the erector head, a preferred type of suction cup is the model B40.10.04AB made by Piab. Two of the suction cups **312** are mounted to a generally longitudinally oriented support block **319a** and the other two suction cups are mounted to a second generally longitudinally oriented support block **319b**.

[0133] Support blocks **319a** and **319b** are generally oriented longitudinally in space apart, parallel relation to each other and each block **319a**, **319b** is joined to other body components of body **300**. Blocks **319a**, **319b** each have open passageways that interconnect each suction cup **312** with an outlet from a vacuum generator **330**. Vacuum generator **330** may be any suitable vacuum generator device such as for example the model VCH12-016C made by Pisco. Vacuum generators **330** each have an inlet interconnected to a hose (not shown) that can carry pressurized air to the vacuum generator. The vacuum generator converts the pressurized air supplied to the inlet port, into a vacuum at one of the outlet ports. That vacuum outlet port is interconnected through the passageway in blocks **319a**, **319b** to a suction cup **312** so that the suction cup can have a vacuum force. Interposed along the pressurized air channel running between each vacuum generator **330** and the source of pressurized air that may be an air compressor (see FIG. **1b**), may be located a solenoid valve device **340** that may for example be a model CPE14-M1BH-5L-1/8 made by Festo. Valve device **340** may be in electronic communication with PLC **132** and be controlled by PLC **132**. In this way PLC **132** can turn on and off the supply of vacuum force to each of the suction cups **312**. To channel the compressed air appropriately, valves in valve device **340** can be driven between open and closed positions by solenoids responsive to signals from PLC **132**. Electrical lines carrying signals to and from PLC **132** could also pass through hose **190** to operate the valve device **340**.

[0134] Still with reference to FIGS. **30** to **33**, downward extending end portions **323** of longitudinal support block **319** have openings **331** that are configured to receive a transversely mounted shaft **342**. Shaft **342** may be mounted for rotation within openings **331**. At one end of shaft **342** may be mounted a gear wheel device **360** that is configured to rotate with shaft **342**. Gear wheel **360** may be interconnected to a drive wheel of a gear box **362** to form a mitre gear connection. Gear box **362** may be driven by a servo motor **364** mounted above gear box **362**. Servo motor **364** may also be a model MPL-B1530U-VJ44AA made by ALLEN BRADLEY and gear box may be a model AER050-030 FOR MPL-A1520 AB SERVO MOTOR made by Apex.

[0135] In FIG. **30**, servo motor **364** is shown with two separate ports **364a**, **364b**. One for the ports may be for supplying a power line and the other for a communication line to facilitate the communication with the servo drive and

PLC **132**. It should be noted that all of the servo motors described in this document may be similarly equipped. Servo motor **364** may, through connection with a servo drive (see FIG. **1b**), be controlled by and be in communication with PLC **132**. An encoder may be provided within or in association with servo motor **364** and the encoder may rotate in relation to the rotation of the respective drive shaft of the servo motor. The encoder may be in communication with, and provide signals to the servo drive and thus to PLC **132**. PLC **132** may be able to determine the rotational position of the shaft **342**. Thus, when appropriate signals are provided from PLC **132**, so servo motor **364** can be operated and can cause shaft **342** to rotate in a particular desired direction at a particular desired rotational speed for a desired amount of time. Thus PLC **132** can control the rotational position of shaft **342**.

[0136] Mounted to shaft **342** between end portions **323** of support blocks **319a**, **319b** is a rotator device generally designated **350**. Rotator device **350** is fixedly attached to shaft **342** and will rotate with shaft **342**. Rotator device **350** includes an arm **351** having one end fixedly mounted to shaft **342**. The opposite end of arm **351** has a mounting block **353** attached to it.

[0137] Secured to mounting block **353** may be a pneumatic actuator **325** that may for example be a model DFM-12-80-P-A-KF, or part #170905 made by Festo. Actuator **325** may be supplied with pressurized air to activate the device that may be controlled by solenoid valve device **340** in the supply line. The solenoid valve **340** may be in communication with and be controlled by PLC **132** (see FIG. **1b**). Actuator **325** may be actuated to reciprocate piston arms **326** between an extended position and a retracted position. PLC **132** may send a signal to valve device **340** to operate actuator **325** to extend piston arms **326** at a particular angular position of arm **351** and/or location of erector head **120b** that is provided by the encoder associated with servo motor **364**. Similarly, PLC **132** may send a signal to valve device **340** to activate arms **326** to be retracted at a particular shaft **342** angular position, and to retract piston arms **326** at a particular angular position, of arm **351** and/or a particular location of erector head **120b**. PLC **342** may cause, acting through valve device **340**, actuator **325** to be actuated at approximately the same time as the cups **320** have contacted the surface of downward facing panel **D** and/or when rotation of arm **351** is just about to begin or has just commenced. Piston arms **326** may be completely extended by the time arm **351** has rotated about 45 degrees.

[0138] Mounted to distal ends of piston arms **326** is a mounting block **328** which may be configured to support a pair of suction cups **320**. Blocks **328** may have open passageways (not shown) that interconnect each suction cup **320** with an outlet from another vacuum generator **330**. Vacuum generator **330** may be any suitable vacuum generator device such as for example the model VCH12-016C made by Pisco. As indicated above, vacuum generators **330** each have an inlet interconnected to a hose (not shown) that can carry pressurized air to the vacuum generator. Vacuum generators **330** convert the supplied pressurized air supplied the inlet port to a vacuum at one of the outlet ports. That vacuum port is interconnected through the passageway in block **328** to a suction cup **320** so that the suction cup can have a vacuum force. Interposed along the pressurized air channel running between each vacuum generator **330** associated with suction cups **320** and the source of pressurized

air may be located the same valve device **340**. Valve device **340** may be interconnected electronically (either with a wireless system or wired communication connection) to PLC **132** and be controlled by PLC **132**. In this way PLC **132** can also turn on and off the supply of vacuum force to each of the suction cups **320**.

[0139] With reference also to FIG. **11**, suction cups **312** can be employed to engage and hold onto the top panel A of blank **111**. Once a blank **111** is retrieved from the top of the stack of blanks, the rotator arm **351** can be rotated approximately 180 degrees such that suction cups **320** of rotator device **350** can engage and hold onto the underside panel D of blank **111**. Once suction cups **320** have engaged panel D the arm **351** can be rotated 90 degrees backwards in the opposite rotational direction and the opposing vacuum forces created by suction cups **312** above and suction cups **320** below, cause the tubular blank **111** to be moved from a flattened configuration to an open configuration as panel D is rotated substantially 90 degrees relative to panel A. The air suction force that may be developed at the outer surfaces of suction cups **320** and **312** will be sufficient so that when activated they can engage and hold top panel A in a stationary position relative to erector head **120b** and rotate panel D relative to panel A to open up the tubular blank to a generally rectangular configuration. The vacuum generated at suction cups **320** and **312** can also be de-activated by PLC **132** at appropriate times by sending signals to valve device **340**.

[0140] Each erector head **120a**, **120b** may be configured to be able to handle a wider range of different sized/dimensioned blanks **111** by providing for additional suction cups **320** and **312** positioned at different locations on the erector heads. Suction cups **320**, **312** could each be “self-sealing” or “self-plugging” suction cups which if not engaging and sealing with a surface of a particular blank that is being processed, may automatically become blocked. This would allow the vacuum/suction forces to be maintained on other suction cups that may have the source of pressurized air/vacuum interconnected thereto and which are engaging a panel of a blank **111**. In this way, each erector head may be adapted to handle a wider variety of sized/dimensioned blanks and cartons/cases that can be formed therefrom.

[0141] The opening of the blank **111** may be assisted by the extension of piston arms **326** of actuator device **325** during rotation of the rotator arm **351**. Preferably when rotator arm **351** has rotated somewhere in the range of about 30-60 degrees back to the 90 degree position, and preferably when it is at approximately 40-50 degrees, and most preferably when it is at about 45 degrees, then the piston arms **326** may be fully extended. This extension of arms **326** and thus of suction cups **320** in a generally tangential direction relative to the rotation of arm **351** compensates for the offset of the axis of rotation of the arm **351** compared to the axis of rotation of the blank that extends along the fold line between panels A and D. The effect of the extension of piston arms **326** once the arm is rotated such as to 90 degrees ensures that the panel D is also oriented at 90 degrees to panel A.

[0142] Once a blank **111** has been opened to the configuration shown in FIG. **11**, then PLC **132** can send a signal to valve device **340** which causes rotary actuator **399** to rotate shaft **316** and thus rotate paddle **310**. Paddle **310** can then engage trailing flap K of blank **111** and cause it to fold about its fold line where it joins to panel D. Thus flap K can be

folded inwards towards the bottom opening of blank **111**. Leading bottom flap J may also be folded about its fold line which joins it with panel B by engagement of the flap with upper and lower folding rails/ploughs **700**, **701** that form part of folding and sealing apparatus **130**. As the blank **111** held by erector head **120b** is moved longitudinally downstream into the folding and sealing apparatus **130** the leading bottom flap J can be folded inwards so that both bottom flaps K and J are folded inwards to start the formation of the bottom of the carton.

[0143] Another feature of erector head **120b** that can be noted is that a carton location sensor apparatus may be provided and may include a reciprocating sensor rod **380** which, when not in contact with a blank, extends downwards through an aperture **381** in plate **327**, below the level of the plane of suction cups **312**. When the erector head **120b** is brought vertically downwards to retrieve a blank on a stack of blanks **111** in magazine **110**, the erector head's movement just prior to suction cups **312** contacting with the upper surface of the blank will be generally vertically downwards. Prior to the suction cups **312** contacting the surface of a panel A of a blank, sensor rod **380** will engage the surface of panel A and cause sensor rod **380** (which may be resiliently displaced due to a spring mechanism biasing the rod downwards) to be pushed upwards. This movement upwards of sensor rod **380** relative to plate **327** will physically cause a sensor (not shown) to be activated and send a signal to PLC **132**. The sensor may be an inductive proximity sensor. The metal cylinder fixed on the rod is sensed by the sensor's circuitry because it changes the inductance of the induction loop inside the sensor. The sensor may be 871FM-D8NP25-P3 made by ALLEN BRADLEY. PLC **132** may respond to that signal by causing servo drives **150** and **154** to slow down so that the final few centimeters (e.g. 3.5 cm) of movement downwards towards contact between cups **312** and the upper surface of panel A occurs at a much slower rate and also PLC knows how much further vertically downwards erector head **120b** must be lowered to establish proper contact between suction cups **312** and panel A. It should also be that sensor rod **380** and associated sensor device can also be used to ensure that PLC **132** is aware of whether once a blank has been engaged in the magazine **110**, it stays engaged with erector head **120** until the appropriate release location is reached, such as once erection of the carton has been completed.

[0144] The particular arrangement of suction cups and rotating paddle on erector heads **120** can be designed based upon the configuration of the carton blank and the particular panels and flaps that need to be rotated. It will also be appreciated that on erector head **120** that is illustrated, suction cups are used to apply a force to hold and/or rotate panels of a carton blank. However alternative engagement mechanisms to suction cups **312** and **320** could be employed.

[0145] With particular reference to Figures including FIGS. **1** to **15** and **17**, system **100** may also include a folding and sealing apparatus **130**. Rail and plough apparatus may be configured to cause all remaining flaps of a blank **111** to be appropriately folded and sealed to produce a carton configuration that is suitable for delivery to a discharge conveyor such as discharge conveyor **117**. Apparatus **130** may include the following components: upper and lower folding rails/ploughs **700** and **701**; a carton support plate **703**; a discharge chute **750**; an upper flap closing device **705**;

a lower flap closing device 707; a right hand compression device 706; and a left hand compression device 704; and a glue applicator 709 (see FIG. 1) having one or more nozzles positioned to apply adhesive to flaps such as flaps J and K. Each of the rails and actuator devices of apparatus 130 may be supported by rods or other members to interconnect the components to support frame 109.

[0146] Upper flap actuation device 705 may include a pneumatic actuator device 704a having its piston arms connected to an upper plough 708a. Similarly, lower flap actuation device 707 may include a pneumatic actuator device 704b having its piston arms connected to an upper plough 708b. Actuator devices 704a, 704b may be the model DFM-25-100-P-A-KF, part #170928 made by Festo.

[0147] Right hand compression device 706 may include a central pneumatic actuator 710 with telescoping extendible support rods 712 and 714 horizontally aligned and disposed on either side of actuator 710. Actuator 710 may be a model DNC-32-100-PPV-A part #163309 made by Festo. With particular reference to FIG. 26, actuator 710 may have piston arms that along with ends of support rods 712 and 714 connected to a longitudinally extending sealing plate 716 having attached thereto longitudinally extending upper rail 717a, and lower rail 717b. Upper rail 717a is positioned to be able to engage upper major flap F and lower rail 717b is positioned to engage lower major flap G when piston arms of actuator device 710 are extended horizontally and transversely inwards to push flaps F and G into engagement with flaps K and J that are positioned underneath.

[0148] Left hand compression ram device 704 has an actuator arm 711 which may be actuated by an actuator device 719 with a vertically and longitudinally disposed plate 720 attached to the end of the actuator arm. Actuator device 719 may be a double acting pneumatic actuator (not shown) that may be provided with pressurized air through hoses, with the air flow being controlled by the solenoid valve device that may be controlled by PLC 132. Other embodiments are possible. For example, with reference to FIG. 26A, a servo-driven actuator for arm 711 may be provided that includes a mounting block 741 that can travel along a rail guide 745 that is secured to a horizontal and longitudinally extending plate forming part of a support frame 746. Mounting block 741 can slide horizontally along rail 745. An L-shaped plate 743 interconnects arm 711 to sliding block 741. Sliding block 741 may also be connected such as with nuts and bolts on its underside to a drive belt 757 made of any suitable material such as for example the same material that may be used in the belts for the moving apparatuses 115—namely a urethane timing belt with steel wires running through it. Continuous drive belt 757 may extend between a freely rotating pulley 759 mounted to an end of frame 746, and a drive wheel of a servo motor 761. Through a servo drive and an absolute encoder. Servo motor 761 may be an Allen Bradley model AB MPL-B320P-MJ22AA and may be interconnected with servo drive to PLC 132. The servo drive may be Allen Bradley model AB. 2094-BM01-S. Motor 761 may be coupled to drive wheel for the belt through an APEX GEARBOX model AE070-005.

[0149] PLC 132 may control the rotation of the drive wheel driven by the servo motor 761 through use of an encoder (that may be an absolute encoder). Thus the movement of belt 757 can be controlled and PLC can determine in real time, the position of ram arm 711 and thus of

compression plate 720. Depending upon the type of, and thickness of material from which blank 111 is formed, the positioning of plate 720 relative to the plate of right hand compression device 706 can be adjusted by PLC 132 to ensure an appropriate degree of compression of the flaps of blank 111 positioned there between.

[0150] Each of actuator devices 704a, 704b, 710 may be double acting cylinders and they may be supplied with pressurized air that is controlled through an electronic valve device (not shown). The valve device may be a model CPE14-M1Bh-5J-1/8 valve unit that may be in communication with and be controlled by PLC 132. In this way, PLC 132 can cause the piston arms to be extended and retracted during the processing of carton blanks to achieve the closure and sealing of the flaps.

[0151] Actuator device 704a and its plough 708a may be appropriately positioned and angled downwards (such as at about 45 degrees to the vertical) to be able to fold down major flap F sufficiently to be able to be engaged by right hand compression device 706. Similarly, actuator devices 704b and its plough 708b may be appropriately positioned and angled upwards (such as at about 45 degrees to the vertical) to be able to fold up major flap G sufficiently to be able to be engaged by right hand compression device 706, substantially simultaneously, or at least allowing of right hand compression device 706 to be able to compress both flaps F and G at the same time towards minor flaps J and K that have upper surfaces containing some adhesive.

[0152] Applicator 709 can have nozzles appropriately positioned and their operation may be controlled by PLC 132. Applicator 709 can apply a suitable adhesive to flaps such as leading minor flap J and trailing minor flap K, once they have been folded inwards to form part of the carton bottom. An example of a suitable applicator 709 that can be employed is the model ProBlue 10 applicator made by Nordson Inc. An example of a suitable adhesive that could be employed with on a carton blank 111 made of cardboard is Cool-Lok 034250A-790 adhesive available from Lanco Adhesives, Inc. Applicator 709 may be in electronic communication with PLC 132 which can signal the applicator to apply adhesive at an appropriate time during the positioning of the erector heads 120a, 120b

[0153] Left hand compression device 704 may be used to enter the carton from the left side and compress flaps F, G, J and K between ram plate 720 of left hand compression device 704 and the rails 717a, 717b of right hand compression device 706. This compression assists in ensuring that the panels are compressed together to ensure that the adhesive appropriately bonds the flaps together to make a solid carton bottom.

[0154] In some embodiments, once the left hand compression device 704 and right hand compression device 706 have completed the compression of the flaps, PLC 132 can send a signal to solenoid valve devices causing the compression devices to be withdrawn. The carton will then have been fully erected and is suitable to be loaded with one or more items. Erector head 120b may then carry the erected carton to a discharge chute 750 and then release it such that it falls onto discharge conveyor 117 which can then move the erected carton away for further processing. In other embodiments such as the one illustrated, the erected carton 111 can be released and fall onto support plate 703 and remain there until the next carton blank carried by another erector head moved by another movement apparatus (such as erector

head **120a** moved by movement apparatus **115a**) moves the next carton blank into the location where it will be folded, sealed and compressed. In doing so the newly arrived carton blank pushes the previous fully erected carton downstream where it may fall onto discharge conveyor **117**. Carton discharge conveyors are well known in the art and any suitable known carton conveyor may be utilized.

[0155] Other examples of transfer devices that might be employed to transfer the carton from apparatus **130** to a carton discharge conveyor include a “blow-off” system that may use one or more jets of compressed air, a suction cup system, the use of pushing arm or simply allowing for freefall of the formed carton.

[0156] A sensor **243** (see FIG. 2) such as an electronic eye model 42KL-P2LB-F4 made by ALLEN BRADLEY may be located near the bottom of discharge chute **750**. Sensor **243** may be positioned and operable to detect the presence or absence of an erected carton at the input to the discharge conveyor **117**. In this way, PLC **132** can be digitally signalled if an erected carton blank **111** is in place at the bottom of the chute **750** such that another erected carton can not be discharged down the chute **750**. If so, the system **100** can be stopped by PLC **132** until any fault at discharge conveyor **117** can be rectified.

[0157] The overall operation of system **100** will now be described further.

[0158] As an initial step PLC **132** may be accessed by an operator through HMI **133** to activate system **100**. The system **100** may be initialized with PLC **132** ensuring that all components are put in their “start” positions. At substantially the same time, a stack of cartons may be placed at the input end of conveyor **204** and system **100** may then be activated (such as by PLC **132** being instructed through HMI **133** to commence the processing of a stack of blanks **111**).

[0159] PLC **132** may then send an instruction to the drive motor of input conveyor **204** to commence to drive belt **214** causing stack of blanks **111** to move downstream. Sometime prior to the stack of blanks reaching alignment conveyor **206**, the right-hand-side magazine side guide wall **201** under control of PLC **132** will be driven by servo motor **260** to expand wide enough to allow the stack of blanks to enter on alignment conveyor **206**, even if the stack is misaligned and/or the blanks in the stack are not perfectly square with each other. The stack of blanks is moved downstream, until once the front edge of the stack of blanks passes the downstream edge of conveyor **204**, sensor **242** will send a signal to PLC **132** indicating that the front edge of the stack has reached the input to alignment conveyor **206**. In response, PLC **132** may then send an instruction to the drive motor of input conveyor **204** to commence to drive belt **216** causing stack of blanks **111** to move downstream towards end wall **218** of magazine **110**. Once the front edge of the stack of blanks **111** reaches end wall **218**, sensor **240** will send a signal to PLC **132** indicating that the front edge of the stack of blanks has reached end wall **218**. In response, PLC **132** can then initiate the tampering sequence to “square up” the stack of blanks, as detailed above.

[0160] In review, the tampering sequence for ensuring the blanks are properly squared up at the pick up location steps, may include the following steps. The tampering actuator **276** may be extended having been activated by pressurized air controlled by PLC **132** and the associated valve. Then the side guide wall **201** may contract to make contact with the side of the case stack and press the side wall **201** against the

left hand side guide wall **200**. This aligns the cases so the side edges of blanks are aligned with each other and the longitudinal side wall of the walls **200** and **201**. The tampering actuator **276** may then retract, and the tampering bar **280** press the stack forward, thereby aligning the blanks in the stack so that their front and rear edges are vertically aligned with each other and with the inner face of the bar **280** and the inside surface of front wall **218**. The stack of blanks **111** is then properly positioned so that the erector heads **120a** and **120b** can begin picking up blanks from the stack.

[0161] One of the erector heads such as erector head **120b** will be positioned by the control of PLC **132** over movement apparatus **115b**, at the zero position calibrated for the head **120b**. PLC **132** may then cause servo motors **150** and **154** to be operated to achieve the following sequence of operations:

[0162] First the head **120b** may be moved to the pick up position as shown in FIG. 17.

[0163] As the erector head **120b** is being brought vertically downwards to retrieve the top blank on a stack of blanks **111** in magazine **110**, the erector head’s movement just prior to suction cups **312** contacting with the upper surface of the blank will be generally vertically downwards. Prior to the suction cups **312** contacting the surface of a panel A of a blank, sensor rod **380** will engage the surface of panel A can cause sensor rod to be pushed upwards. This movement upwards of sensor rod **380** relative to plate **327** will physically cause the sensor to be activated and send a signal to PLC **132**. PLC **132** may respond to that signal by causing servo drives **150** and **154** to slow down so that the final few centimeters (e.g. 3.5 cm) of movement downwards towards contact between cups **312** and the upper surface of panel A occurs at a much slower rate. Also PLC knows how much further vertically downwards erector head **120b** must be lowered to establish proper contact between suction cups **312** and panel A. It should also be that sensor rod **380** and associated sensor device can also be used to ensure that PLC **132** is aware of whether once a blank has been engaged in the magazine **110**, it stays engaged with erector head **120** until the appropriate release location is reached, such as once erection of the carton has been completed.

[0164] PLC **123** will also operate the valve device **340** on head **120b** to cause suction force to be developed at suction cups **312** and optionally also **320** (although suction at suction cups **320** can be delayed);

[0165] With the head **120b** in the pick up position shown in FIG. 17 and the suction force being applied at suction cups **312**, the head **120b** can engage the panel A (see location of suction cup outline on FIG. 10A) and then commence to lift upwards the blank as shown in FIG. 18. PLC **132** will know how high to lift the upper surface of blank **111**, to ensure that once opened up, the datum line W1 will be appropriately vertically located so that components of folding and sealing apparatus **130** will be able to fulfil their functions as described above.

[0166] Preferably when erector head **120b** has reached a determined vertical position, and preferably while the erector head **120b** is not moving longitudinally towards folding and sealing apparatus **130**, PLC **132** will send a signal to cause servo motor **134** to rotate which will then cause shaft **342** to rotate in a particular desired

direction at a particular desired rotational speed for a desired amount of time. PLC 132 can control the rotational position of shaft 342 to cause rotator device 350 which is fixedly attached to shaft 342 to rotate with shaft 342. Thus rotator device 350 may be rotated to the position shown in FIG. 19 and at that position suction cups 320, which will have suction engaged, will attach to the underside of blank 111, and in particular to panel D.

[0167] The next operation is the blank opening whereby through control of PLC 132, opposed forces provided by suction cups 312 acting upwards on top and suction cups 320 acting in an opposite downward direction will start to pull the flattened blank apart. The forces are then continued by the suction cups 312 above and 320 below, as rotator device 350 is rotated 90 degrees backwards to the position shown in FIG. 20.

[0168] During the backwards rotation of rotator device 350, actuator device 325 may be supplied with pressurized air controlled through valve device 340 to activate the actuator device. PLC 132 may send a signal to valve device 340 to operate actuator device 325 to extend piston arms 326 at a particular angular position of arm 351 and or location of erector head 120b that is provided by the encoder associated with servo motor 364. PLC 342 may cause, acting through valve device 340, actuator device 325 to be actuated at approximately the same time as the cups 320 have contacted the surface of downward facing panel D and the rotation of arm 351 is just about to begin or has just commenced. Piston arms 326 may be completely extended by the time arm 351 has rotated about 45 degrees. The piston arms 326 may continue to be extended and stay extended when rotator device 350 is at the 90 degrees position shown in FIG. 20.

[0169] Once the blank 111 has been opened, erector head 120b can securely hold the blank by the suction forces exerted by cups 312 and 320, to panels A and D. Also, once opened the flaps K and J need to be folded inwards towards the bottom opening of the carton. In the embodiment shown in Figures such as FIGS. 17 to 29, the trailing minor flap K is closed by actuation of paddle 310 as shown in FIG. 21. Thus PLC 132 can send a signal to valve device 340 which causes rotary actuator 397 to rotate shaft 316 and thus rotate paddle 310. Paddle 310 can then engage trailing minor flap K of blank 111 and cause it to fold about its fold line where it joins to panel D. Thus, flap K can be folded inwards towards the bottom opening of blank 111.

[0170] Leading bottom flap J may also be folded about its fold line which joins it with panel B by engagement of the flap with upper and lower folding rails/ploughs 700, 701 that form part of folding and sealing apparatus 130 as erector heads 120b is moved longitudinally downstream towards apparatus 130. As the blank 111 held by erector head 120b is moved longitudinally downstream into the folding and sealing apparatus 130 the leading bottom flap J can be folded inwards by rails/ploughs 700, 701, so that both bottom flaps K and J have been folded inwards to start the formation of the bottom of the carton, as is shown in FIG. 22.

[0171] Also when the flaps K and J have been folded inwards, under the control of PLC 132, or pursuant to another control or trigger, adhesive applicator 709 can

through appropriately positioned nozzles, apply a suitable adhesive at appropriate positions on the flaps K and J such as shown. The application of glue can occur before, during, or after PLC 132 has caused movement apparatus 115b to move erector head 120b to a downstream location where the major flaps F and G can be folded and compressed onto minor flaps K and J. As shown in FIG. 23, glue may be applied while movement apparatus 115b is moving erector head 120b to the downstream location for closing the bottom opening by folding and compression.

[0172] Next upper flap actuation device 705 may be activated by PLC 132 acting through a valve device to cause pneumatic actuator device 704a to extend piston arms connected to an upper plough 708a. Similarly, lower flap actuation device 707 may also be activated substantially simultaneously by PLC 132 such that pneumatic actuator device 704b extends its piston arms connected to lower plough 708b as shown in sequential FIGS. 24 and 25.

[0173] Next, as shown in FIG. 26, right hand compression device 706 with its central pneumatic actuator 710 may have piston arms extended so that longitudinally extending sealing plate 716 having attached thereto longitudinally extending upper rail 717a, and lower rail 717b engages the upper and lower major flaps F and J. Upper rail 717a is positioned to be able to engage upper major flap F and lower rail 717b is positioned to engage lower major flap G when piston arms of actuator device 710 are extended horizontally and transversely inwards to push flaps F and G into engagement with flaps K and J that are positioned underneath. Upper and lower flap actuation devices 705 and 707 may be withdrawn by PLC 132 when compression device 706 has engaged flaps F and G.

[0174] Next, as shown in FIG. 27, left hand compression device 704 may be used to enter the carton from the left side and compress flaps F, G, J and K between ram plate 720 of left hand compression device 704 and the rails 717a, 717b of right hand compression device 706. This compression assists in ensuring that the panels are compressed together to ensure that the adhesive appropriately bonds the flaps together to make a sold carton bottom.

[0175] Once the compression has been held for a short time (for example about 0.5 seconds) to allow the glue to sufficiently set/harden and bond the flaps together, the compression can be released by withdrawing left hand compression device 704 and right hand compression device 706 as shown in FIG. 28. The carton is then fully erected and released from both apparatus 130 and from erector head 120b as PLC 132 will cause suction cups 320 and 312 to have their suction force turned off by valve device 340. Additionally, PLC 132 can cause rotator device 350 to be rotated backwards a further 90 degrees to the horizontal ready position shown in FIG. 29.

[0176] Thereafter, erector head 120b can release the erected carton which can then fall onto support plate 703 and remain there until the next carton blank carried by another erector head moved by another movement apparatus (such as erector head 120a moved by movement apparatus 115a) moves the next carton blank into the location where it will be folded, sealed and compressed, and in doing so pushes the previous fully

erected carton downstream to chute **750** where it may fall onto discharge conveyor **117**.

[0177] The entire sequence of movement of a blank **111** as it is processed by system **100** is shown in isolation in FIGS. **10A-D**, and FIGS. **11** to **16**. In FIGS. **10A-D** the blank is shown in its flattened tubular configuration. In FIG. **11** it is shown in its opened configuration after being opened by an erector head like erector head **120**. In FIG. **12** it is shown with the trailing minor flap **K** folded inwards and in FIG. **13** it is shown with leading minor flap **J** also folded inwards. In FIG. **14** blank **111** is shown with the major bottom flaps **F** and **G** folded inwards and in FIG. **15** the blank is shown when the flaps **J**, **K**, **F** and **G** are being or have been compressed to seal the bottom of the carton. Finally in FIG. **16** the erected carton is shown with its opening facing upwards so that it may be loaded with one or more items.

[0178] While the foregoing handling of a carton blank **111** by erector head **120b** has been occurring, erector head **120a**, being supported and moved by movement apparatus **115a**, can be carrying out the same process but do so out of phase with erector head **120b**. For example, the cyclical movement and operation of erector head **120a** may be 180 degrees out of phase with the movement and operation of erector head **120b**. By providing two erector heads **120a** and **120b** operating simultaneously, but out of phase so one does not interfere with the other, the processing capacity of blanks can be increased significantly. But in using only one erector head **120**, the processing capacity of the system **100** may still be relatively high. In part the relatively high processing capacity is also due to the relatively short “stroke” (i.e. longitudinal distance) that the erector heads must travel when carrying out the blank retrieval, erection, folding, sealing and compression. This means that the components do not have to travel such a great distance as in conventional carton erectors. When using two erector heads with moving apparatuses, **100** may be capable of processing about 35 cartons per minute.

[0179] Many variations of the embodiments described above are possible. By way of example only an alternate configuration for an erector head **1120** and folding and sealing apparatus **1130** is shown in FIGS. **34a** to **44**.

[0180] With reference to FIGS. **34a** and **34b**, erector head **1120** is built in substantially the same way as erector head **120** and functions in the same way apart from the following major differences. Erector head **1120** does not include a paddle member like paddle **320** on erector head **120**. As will be described hereinafter, the component and functionality for closing minor trailing flap **K** of a blank **111** can be moved off the erector head and may become part of a modified folding and sealing apparatus **1130** (see for example FIG. **36**).

[0181] Erector head **1120** may have body generally designated **1330**, that includes a bottom suction plate **1327** that is generally shaped in a square cross configuration to provide flanged openings for such cups. In each of the open flanges of plate **1327** is positioned a suction cup **1312**. Suction cups **1312** are mounted with support blocks **1321** to a mounting plate **1322**. Also mounted with mounting blocks is a suction cup **1313** and optionally cups **1315**. Cups **1313** and **1315** may be employed to support a panel **B** of a blank **111** if the configuration of the panel and/or materials from which blank **111** is made, require additional support for the blank **111** at least when it is retrieved from the stack of blanks **111** in the magazine and even until the rotary actuator

device **1350** (which may be substantially the same as rotary actuator **350** on erector head **120**) engages the bottom panel **D** of the blank prior to opening the blank.

[0182] In some applications, without the additional support provided by cup **1313** and possibly cups **1315**, the panels **B** and **C** may not remain in a generally flattened configuration when the blank is picked up by cups **1312** engaged with panel **A**.

[0183] It should be noted that suction cups and vacuum generators used on erector head **1120** may be same as used on erector head **120**. For simplicity, electrical cables and hoses for pressurized air are not shown on erector head **1120** but like erector head **120** can be installed in appropriate locations.

[0184] Also, a valve device like valve device **340** above, to control the flow of air is not shown but may be employed on erector head **1120** and may be in electronic communication with PLC **132** and be controlled by PLC **132**. In this way PLC **132** can turn on and off the supply of vacuum force to each the vacuum generators associated with each of the suction cups on erector head **1120**.

[0185] The sequence of opening a blank using erector head **1120** is shown in FIGS. **35a**, **35b**, and **35c**. Actuator **1325** may be actuated to reciprocate piston arms **1326** between an extended position and a retracted position. PLC **132** may send a signal to valve device to operate actuator **1325** (like actuator **325**) to extend piston arms **1326** at a particular angular position of arm **1351** and/or location of erector head **1120b** that is provided by the encoder associated with servo motor **1364** (like servo motor **364**). Similarly, PLC **132** may send a signal to valve device (not shown) to activate arms **1326** to be retracted at a particular shaft **1342** angular position, and to retract piston arms **1326** at a particular angular position, of arm **1351** and/or a particular location of erector head **1120**. PLC may cause, acting through valve device, actuator **1325** to be actuated at approximately the same time as the cups **1320** have contacted the surface of downward facing panel **D** and/or when rotation of arm **1351** is just about to begin or has just commenced. Piston arms **1326** may be completely extended by the time arm **1351** has rotated about 45 degrees. At the same time or sometime before, rotary actuator **1350** is activated to start the rotation, the PLC may through the valve device cause suction to be released from suction cup **1313** to allow panel **B** of blank **111** to rotate relative to panel **A**.

[0186] By way of further explanation, the two erector heads of system **100** can each in turn be employed to engage and hold onto the top panel **A** of blank **111**. Once a blank **111** is retrieved from the top of the stack of blanks, the rotator arm **1351** can be rotated approximately 180 degrees such that suction cups **1320** of rotator device **1350** can engage and hold onto the underside panel **D** of blank **111**. Once suction cups **1320** have engaged panel **D**, suction at suction cup **1313** can be released and the arm **1351** can be rotated 90 degrees backwards in the opposite rotational direction and the opposing vacuum forces created by suction cups **1312** and possibly **1315** above, and suction cups **1320** below, can cause the tubular blank **111** to be moved from a flattened configuration to an open configuration as panel **D** is rotated substantially 90 degrees relative to panel **A**. The air suction force that may be developed at the outer surfaces of suction cups **1320** and **1312** and possibly **1315** will be sufficient so that when activated they can engage, hold top panel **A** in a stationary position relative to erector head **1120** and rotate

panel D relative to panel A to open up the tubular blank to a generally rectangular configuration. The vacuum generated at suction cups **1320**, **1312**, **1313** and possibly **1315**, can also be de-activated by PLC **132** at appropriate times by sending signals to valve device, such as when it is appropriate to release the fully erected carton.

[**0187**] As with erector head **120**, on erector head **1120**, opening of the blank **111** may be assisted by the extension of piston arms **1326** of actuator device **1325** during rotation of the rotator arm **1351**. Preferably when rotator arm **1351** has rotated somewhere in the range of about 30-60 degrees back to the 90 degree position, and preferably when it is at approximately 40-50 degrees, and most preferably when it is at about 45 degrees, then the piston arms **1326** may be fully extended. This extension of arms **1326** and thus of suction cups **1320** in a generally tangential direction relative to the rotation of arm **1351** compensates for the offset of the axis of rotation of the arm **1351** compared to the axis of rotation of the blank that extends along the fold line between panels A and D. The effect of the extension of piston arms **1326** once the arm is rotated such as to 90 degrees ensures that the panel D is also oriented at 90 degrees to panel A.

[**0188**] Another feature of erector head **1120** that can be noted is that a carton location sensor apparatus may be provided and may include a reciprocating sensor rod **1380** which, when not in contact with a blank, extends downwards through an aperture **1381** in plate **1327**, below the level of the plane of suction cups **1312**. In a manner similar to sensor rod **380** in erector head **120b**, when the erector head **1120** is brought vertically downwards to retrieve a blank on a stack of blanks **111** in magazine **110**, the erector head's movement just prior to suction cups **1312**, **1313** and possibly **1315**, contacting with the upper surface of the blank will be generally vertically downwards. Prior to the suction cups contacting the surface of a panel A of a blank, sensor rod **1380** will engage the surface of panel A which can cause the sensor rod to be pushed upwards. This movement upwards of sensor rod **1380** relative to plate **1327** will physically cause a sensor (not shown) to be activated and send a signal to PLC **132**. Like in the previous embodiment, the sensor may be an inductive proximity sensor. The metal cylinder fixed on the rod is sensed by the sensor's circuitry because it changes the inductance of the induction loop inside the sensor. The sensor may be 871FM-D8NP25-P3 made by ALLEN BRADLEY. PLC **132** may respond to that signal by causing the movement apparatus (not shown but may be like apparatus **115b**) to slow down so that the final few centimeters (e.g. 3.5 cm) of movement downwards towards contact between cups **1312** and the upper surface of panel A occurs at a much slower rate and also PLC knows how much further vertically downwards erector head **1120** must be lowered to establish proper contact between suction cups and panel A. It should also be that sensor rod **1380** and associated sensor device can also be used to ensure that PLC **132** is aware of whether once a blank has been engaged in the magazine **110**, it stays engaged with erector head **1120** until the appropriate release location is reached, such as once erection of the carton has been completed.

[**0189**] With reference now to FIGS. **36** to **44**, it will be observed that unlike with erector head **120**, with erector head **1120**, each opened blank is moved towards folding and scaling apparatus **1130** to fold both leading minor panel J and trailing minor panel K with the folding and scaling apparatus **1130**.

[**0190**] Folding and sealing apparatus **1130** mounted to a plate **1175** forming part of frame **1109** may be constructed in the same manner as apparatus **130** mounted to frame **109**, as described above. However, apparatus **1130** may be provided with an angled paddle device **1310** that is connected to a distal end of a paddle arm **1314**, that may be mounted to frame **1109**. Paddle arm **1314** may be connected to a shaft **1316** a rotary actuator **1399** for rotation therewith. The rotary actuator may be a double acting rotary pneumatic actuator manufactured by Festo under engineering part #DSM-32-270-CC-FW-A-B. Actuator **1399** can cause rotation of arm **1314** clockwise and counter-clockwise around its axis of up to 270 degrees. Rotary actuator **1399** may be supplied with pressurized air supplied by hoses (not shown) connected to ports **1395** and **1397**. Those hoses may also be connected to a solenoid valve device (not shown) which may be controlled by the PLC **132**. In this way the rotation clockwise and counter-clockwise of paddle **1310** may be controlled by PLC **132**.

[**0191**] Once a blank **111** has been opened to the configuration shown in FIG. **36**, then PLC **132** can send a signal to cause erector head **1120** to move towards apparatus **1130**. As shown in the sequence of FIGS. **37** to **39**, initially, leading minor flap J will be engaged by ploughs **1700** and **1701** to fold flap J inwards. While or after that is being completed, as shown in the sequence in FIGS. **40** to **42**, next the valve device can cause actuator **1399** to rotate shaft **1316** and thus rotate arm **1314** with paddle **1310** attached thereto. Paddle **1310** can then engage trailing flap K of blank **111** and cause it to fold about its fold line where it joins to panel D. Thus flap K can be folded inwards towards the bottom opening of blank **111**. Thereafter as shown partially in FIGS. **43** to **44**, the carton blank **111** held by erector head **1120b** can be moved longitudinally further downstream into the folding and scaling apparatus **130** where the minor flaps may be glued and the major top and bottom flaps F and G may be folded inwards and compressed, in substantially the same manner as described above in relation to erector head **120b** and movement apparatus **115b**.

[**0192**] The particular arrangement of suction cups and rotating paddle on erector heads **1120** can be designed based upon the configuration of the carton blank and the particular panels and flaps that need to be rotated. It will also be appreciated that on erector head **1120** that is illustrated, suction cups are used to apply a force to hold and/or rotate panels of a carton blank. However alternative engagement mechanisms to suction cups may be used.

[**0193**] In some embodiments, the flaps of the blank may be sealed by means other than a glue applicator. For example, it is possible to configure folding and scaling apparatus with an adhesive tape applicator that may apply tape to the bottom of the box once all minor and major flaps have been folded. In such an embodiment, compression of the flaps at the bottom of the erected carton may not be necessary. An example of such a set up is illustrated in FIGS. **50** to **52**. In this embodiment the folding and sealing stations like station **130** have been replaced by a folding and sealing station that includes a middle plough for folding a leading minor flap. Thus both minor flaps can be closed by the middle plough for the leading minor flap and a paddle device like those described above for the trailing minor flaps. Upper and lower ploughs can be provided to fold over top of the minor flaps and then the moving apparatus can move an erector head **120** carrying an opened and flap folded blanks

against the operational surface of an adhesive tape applicator. An example of a tape applicator that could be adapted for such use is a model Z59-557 supplied by Dekka Industries Inc. The folded bottom of the opened blank can then be moved longitudinally against the carton blank and tape could be started to be applied at a lower portion of panel B, over and along the middle join between flaps F and G, and the terminate at a lower portion of panel D.

[0194] In another embodiment, shown only schematically in FIG. 45, the system could be modified to employ one or more moving apparatuses 2115a, 2115b that may be substantially the same as moving apparatus 115a, 115b, and a magazine 2110 that may be substantially like magazine 110. However, folding and sealing apparatus 130 or 1130 could be replaced/or another device could be inserted above a support plate 2703 that has a discharge chute 2750. A blank shoe device 2130 may be configured with interior guides. Erector head 2120a, 2120b, may be simplified devices controlled by PLC 132 which have only four suction cups 2130 that may be arranged in a generally rectangular configuration. Erector heads 2120a, 2120b may be readily interchanged in system 100 illustrated and described above for erector heads 120a, 120b and PLC 132 may operate another sequence of operations on erector heads 2120a, 2120b to process a blank 1111 (see FIG. 46) that may be used to form an open top tray. Suction cups 2130 may engage a blank 1111 that is configured to be formed into an open top tray. The moving apparatuses 2115a/b may move a blank secured to a head 2120a/b longitudinally from the magazine where it is retrieved from a stack of blanks, through opposed glue applicators 2709 which may apply a suitable adhesive to flaps and then move the blank above shoe device 2130. The moving apparatus may then move the blank downwards through the shoe device 2130 causing the flaps to be folded and they can be held within the shoe for a sufficient time to allow the glue to set. Thereafter continued movement downwards can push the blank clear of the shoe device 2130 and then suction cups can release the blank which can then fall onto support plate 2703. Thereafter the blank can be moved for example by a blow-off nozzle discharging high pressure air (under control of PLC 132 through a valve device interposed in pressurized air hoses) to discharge the blank to chute 2750 for transfer to a discharge conveyor.

[0195] It will be appreciated that by making a relatively small number of changes to the components of the system, the system can be altered from being able to process blanks for open top cartons to being able to process blanks that can be turned into open top trays. Examples of other blanks that may be processed, cartons that may be formed are illustrated in FIGS. 47, 48 and 49 and include blanks for wrap around half slotted cases (HSC) and HSC blanks, as well as blanks for a wrap around RSC.

[0196] Turning now to FIG. 58, an order fulfilment system generally designated 1000 may include several components including an order fulfilment processor 1300, and corresponding sets of case formers 1100A, 1100B and 1100C, case loaders 1400A, 1400B and 1400C and case sealers 1500A, 1500B and 1500C. A plurality of customer order devices 1200A, 1200B and 1200C may be provided that may be linked with order fulfilment processor 1300. Customer order device 1200A may for example be a telephone that may be capable of communication with a call center 1250. Call center 1250 may be adapted to receive orders from customer operating customer order device 1200A and then

by virtue of call center software, a call center operator may input an order for one or more products that may be communicated by a communication link to order fulfilment processor 1300. Customer order devices 1200B and 1200C may for example be personal computing devices including mobile phones, personal computers, etc. that may be capable of direct communication such as by communication over a wireless and/or land-based communication network with order fulfilment processor 1300. This network may, for example, an IPV4, IPV6, X.25, IPX compliant or similar network. Thus, this network may be the public Internet. Through operation of appropriate software on the customer order devices 1200B, 1200C and order fulfilment processor 1300, the customer order devices 1200B, 1200C may be adapted to input an order for one or more products into order fulfilment processor 1300. For example, customer order devices 1200B and 1200C may be adapted to execute a suitable HyperText Transfer Protocol (HTTP)-enabled browser to access data and services provided by an HTTP server application executed by order fulfilment processor 1300, and thereby input orders for one or more products into order fulfilment processor 1300.

[0197] Order fulfilment processor 1300 may be a main-frame computer, a server, or other computing device capable of processing customer orders received directly or indirectly from customer order devices 1200A-C. Order fulfilment processor 1300 may include a database that includes information that may be stored in a suitable memory therein including information relating to: (a) information/details of all products that may be ordered by a customer through system 1000 including one or more characteristics of each product such as the physical volume occupied by the space and/or the actual physical dimensions (e.g. height, width, length, and/or diameter) of each product (such as the dimensions of the box in which one or more items is held), optionally the weight of each product, and further optionally product codes associated with each product, such as a Universal Product Codes (UPC) or, if the product is a book, an International Standard Book Number (ISBN); (b) information/details of each of a plurality of types/sizes/configurations of cases/case blanks that can or are being used in system 1000 to package one or more products ordered by a customer including the dimensions of each type of case/case blank; (c) information/details of each case former (e.g., case formers 1100A-C), including information/details of the cases that each case former is capable of forming (such as the type, size and/or configuration), and optionally when a case former includes multiple magazines, as detailed below, the type, size and/or configuration of case blank provided in each of those magazines and the corresponding type, size and/or configuration of case that can be formed from each type of case blank, and further optionally the quantity of case blanks provided in each of those magazines; (d) information/details about each customer including the name of the entity and shipping address to which an order fulfilled by system 1000 is to be shipped and (e) information/details about where each product is located in a product storage facility such as a warehouse building holding products that may be ordered.

[0198] As noted, order fulfilment processor 1300 may also include an HTTP server application adapted to provide database information to customer order devices 1200B and 1200C, and to receive orders from customer order devices 1200B and 1200C. Some or all of the aforementioned

information/details may be input into order fulfilment processor **1300** manually by an operator of system **1000**. Additionally or alternatively with respect to information/details of each available case may be updated periodically or on an ongoing basis. PLC **132** of each carton former **1100A-1100C** may during operation, be adapted to monitor the status of the case blanks in its magazine(s) and provide information relating to that status to order fulfilment processor **1300**. In this way, order fulfilment processor **1300** may be continually be provided with up-to-date information on available case blanks that are in the magazines of each of the carton formers.

[0199] Order fulfilment processor **1300** may also include a product packaging utility/product packaging software module that identifies a suitable type of case (or types of cases) for packaging the products in an order placed by a customer from a plurality of available cases. An example of such a product packaging utility is disclosed in U.S. Pat. No. 6,876,958 to Chowdhury et al., issued to assignee New Breed Corporation on Apr. 5, 2005 (hereinafter, “Chowdhury”), the contents of which is hereby incorporated by reference herein in its entirety. In particular, Chowdhury’s product packaging utility processes each order placed by a customer to automatically identify, from available case types/sizes/configurations, a type/size/configuration of suitable case (or cases) suitable for packaging the products in the order. Chowdhury’s product packaging utility identifies/determine suitable case(s) according to an algorithm/function that accesses and uses one or more electronically-stored characteristics of each product in the order (e.g., dimensions, weight, etc.) and one or more electronically-stored characteristics of available case types (e.g., dimensions, size, configuration, type, maximum volume that can be held, maximum weight that can be held, etc.). This algorithm identifies suitable cases such that a minimum number of cases and the smallest size cases suitable for packaging the products in the order may be provided. Thus, identification of suitable case types/sizes/configurations can be optimized to provide an optimal case type/size/configuration which minimizes packaging material used and to minimize empty space in cases, and a case identified as suitable may be referred to as an “optimal” case. It will be appreciated that identification of suitable case types/sizes/configurations may also be identified or optimized according other pre-defined criteria. The case identification algorithm of Chowdhury’s product packaging utility may also take into account other factors and constraints such as, e.g., the availability of each type/size/configuration of case, the maximum fill ratio of each type/size/configuration of case, the maximum number of products that can be placed into each type/size/configuration of case, and whether certain products are pre-packaged together and therefore must be placed in the same case. Thus, when order fulfilment processor **1300** includes a product packaging utility such as Chowdhury’s product packaging utility, order fulfilment processor **1300** may process a customer order for specific products by accessing information in its memory and utilizing an algorithm/function to identify a suitable case (or cases) for packaging those products from a plurality of available cases.

[0200] It should be noted that the size of the case may be the overall internal available volume of the case in which items may be held. The size may also be the specific dimensions of the case. The type of case may include the reference to what material the blanks is made from (e.g.

paperboard or corrugated cardboard). Its configuration may an indication of it being a top opening case which is generally cuboid in shape when closed, or another configuration such as a regular slotted case, etc.

[0201] Chowdhury’s product packaging utility may also generate, for each case of a particular type/size/configuration identified to fulfil an order, a packing list indicating the order in which each of the products is to be preferably placed into the case, as well as placement information indicating where each product is to be preferably placed in the case. For example, this placement information may be expressed using coordinates (e.g., 0, 0, 0) in a coordinates system defined for the case and/or descriptors of locations in the case (e.g., front, right hand side, second layer, etc.). Thus, when order fulfilment processor **1300** includes a product packaging utility such as Chowdhury’s product packaging utility, order fulfilment processor **1300** may generate a packing list and/or placement information for each identified case. Order fulfilment processor **1300** may also generate a diagram illustrating a desired optimal physical arrangement of the products in each case. Such a diagram may be readily generated using placement coordinates for each product, as provided by Chowdhury’s product packaging utility.

[0202] For each case of a particular type identified to fulfil an order, order fulfilment processor **1300** may also be configured to be able to select one of case formers **1100A**, **1100B** or **1100C** to form a suitable case of the type/size/configuration identified by order fulfilment processor **1300**. Order fulfilment processor **1300** may access and use information stored in its memory regarding the suitability of the case formers to handle an identified suitable case. For example, suitability of a case former may be determined by order fulfilment processor **1300** based on stored information regarding whether the case former includes magazines designated to hold the types/size/configuration of case blanks required forming the identified case. Suitability of a case former may also be determined based on stored information regarding the quantity of the required type/size/configuration of case blank in a magazine of the case former. Such quantities may be measured using suitable sensors placed at each case former, and updated during operation. Alternatively, order fulfilment processor **1300** may simply select a case former randomly or according to a pre-defined sequence.

[0203] Once a suitable case former (e.g., one of case formers **1100A**, **1100B** or **1100C**) has been selected, order fulfilment processor **1300** may generate a Fulfilment Order data structure (e.g. a file, object, message or the like) containing information for/instructions to the case former to form and label a required case. A generated Fulfilment Order data structure may be communicated by a communication link to the PLC of one of the case formers **1100A**, **1100B** or **1100C**.

[0204] The Fulfilment Order data structure may include indicators indicating (i) the type/size/configuration of case determined by the product packaging utility that is required to be formed and labelled by the case former **1100A**, **1100B**, **1100C**; (ii) the particular magazine of the case former containing case blanks for forming the required suitable case; (iii) a list of the particular product(s) from the customer order being fulfilled that are required to be loaded into the required case once formed, optionally identified by associated product codes and optionally arranged in the order in which the products should be loaded into the case once

formed; (iv) optionally information such as packing list or a diagram illustrating/specifying a desired optimal physical arrangement of the products in loading the case; (v) optionally the location in the storage facility/warehouse building of each particular product from the customer order being fulfilled; and (vi) customer shipping information for that case indicating the destination name and address for that case. In some cases, the Fulfilment Order data structure may include information for multiple cases to be handled by the selected case former.

[0205] A Fulfilment Order data structure may be received and processed by the PLC of the case former to which the data structure is sent. In particular, the PLC of the case former processes the Fulfilment Order data structure to identify a requested type/size/configuration of case (or cases) to be formed, the particular magazine of the case former containing case blanks for forming each required case, and the contents of the label (or labels) to be applied. Once a required suitable case and the particular magazine containing case blanks for forming the required suitable case have been identified, the PLC of the selected case former **1100A**, **1100B** or **1100C** can then cause a suitable case blank to be formed into the requested type/size/configuration of case and labelled, as further described hereinafter.

[0206] Optionally, the data structure may be stored in memory of the PLC of the case former or in memory of order fulfilment processor **1300** for later retrieval when the order is picked and packed, as described below.

[0207] Once the case has been formed and labelled for a particular customer product order, it may then be physically transferred to a respective case loader generally designated **1400A**, **1400B** or **1400C**. In some embodiments, the formed and labelled case can be picked up by a person (referred to herein as an Order Fulfilment Picker or “OFP”) who may be in a product storage facility (e.g. a warehouse building) filled with the products handled by order fulfilment system **1000**. OFP may have or carry a label scanner device **1407** (see FIG. **62B**) which may include a scanner **1411** and an interconnected display device **1409**. Examples of suitable label scanning devices that could be employed include the model LT5020H made by Worth Data Inc. (Santa Cruz, CA, USA).

[0208] Label scanning device **1407** may be a bar code reader adapted to scan and derive information from the label or labels applied to the case. Optionally, label scanning device **1407** may be connected to one or other of the PLC of the case former or order fulfilment processor **1300** by a communication link. In such instance, some or all of the information for a case may be retrieved by label scanning device **1407** from the PLC of the case former or from order fulfilment processor **1300** using a case identifier encoded in bar codes on the label(s) applied to the case.

[0209] The OFP may for example scan the bar codes on the label(s) on the case which may enable the OFP to identify the particular products that are to be loaded into that case. Optionally, scanning these bar codes may also enable the OFP to identify where the particular products are located in the warehouse building. The OFP may then load the case into a cart **1413** (FIG. **62B**) and then proceed to locate the products in the warehouse and fill the case with those products, possibly in the order listed by the scanning device **1407**. Optionally, a packaging arrangement diagram (such as the diagram of FIG. **61**) either illustrated on the label on the case, or optionally displayed on a device such as the label

scanner, if available, may be provided to and used by the OFP to load the case in a desired optimal manner. An example of a packaging arrangement diagram that can be utilized to load a case is illustrated in FIG. **61**. A case, formed from a blank, and having dimensions of width W, height H and Length L, can be loaded as shown with items (i.e. products) numbered 1 to 6 arranged in a particular arrangement and may also include some additional dunnage or packing material (e.g. bubble wrap type material) that may be inserted by an OFP to maintain the stability and integrity of the items in the packaging arrangement during shipping to the customer.

[0210] In other embodiments, one or more of the case loaders **1400A**, **1400B**, **1400C** may include automated equipment such as one or more robotic systems instead or in addition to an OFP.

[0211] Turning now to FIGS. **53** to **57**, case former **1100** (representative of each of case formers **1100A-C**) may comprise the same or substantially the same components as carton forming system **100** as described above, except where differences are hereinafter described. Like in carton forming system **100**, the structural/mechanical components of carton former **1100** may be made from any suitable materials. Case former **1100** is particularly useful as part of a customer order fulfilment system **1000** that may fulfil product orders placed or initiated by customers as described above. However, carton former **1100** may also be used in other applications.

[0212] As an alternate to a magazine like magazine **110** in carton forming system **100** as described above, case former **1100** may include or utilize a plurality of magazines such as magazines **M1-M16**. Magazines **M1-M16** may each contain one or more stacks of product packaging, such as case blanks which each may generally be like blanks **111** processed by system **100**, with at least some of the magazines **M1-M16** containing different types/sizes and/or configurations of packaging/case blanks to other magazines. The size, configurations and types of case blanks (and the cases that can be formed therefrom) can vary to provide a range of case sizes, configurations and types that can be automatically processed by carton former **1100** without the need for any manual intervention to modify any components of the case former **1100**. PLC **132** of case former **1100** may be programmed such that the particular dimensions/overall size/configuration (e.g. such as regular slotted carton or “RSC”)/type of each of the blanks held in each one of the magazines **M1-M16** is stored in the memory of the PLC **132**.

[0213] It should also be noted that case former **1100A**, **1100B**, and **1100C** may each be configured with magazines having a different set/selection of sizes/configurations/types of case blanks from that of the other magazines, so that each of the carton formers **1100A**, **1100B**, **1100C** are operable to process different cases. Case formers **1100A**, **100B**, and **1100C** may be configured with magazines such that they collectively process a pre-defined set of case blanks types that provides a range of case sizes, configurations and types.

[0214] Each magazine **M1-M16** may have its own blank transfer apparatus that may each include a transversely oriented magazine conveyor **1203(1)** to **1203(16)** respectively. Each conveyor **1203(1)** to **1203(16)** (referred to generically as a magazine conveyor **1203**) may be controlled by PLC **132** of its carton former **1100**, such that a stack of blanks in each magazine **M1-M16** may be moved to a position adjacent a longitudinally oriented, central case blank in-feed conveyor **1204**. Each magazine **M1-M16** may

have a transfer apparatus under the control of PLC 132 that is operable to extract and move a blank from a stack in the magazine M1-M16 adjacent to in-feed conveyor 1204 and feed it onto central in-feed conveyor 1204 to that it may be transported to be labelled as described hereinafter, and also folded and sealed in a manner like that described above in connection with system 100.

[0215] With reference now to FIG. 54A, by way of representative example of the construction of a magazine, magazine conveyor 1203(1) may include a frame 1215 that supports five, generally parallel, and spaced continuous belts 1213 that may be made of any suitable flexible material such as Ropanyl. The belts 1213 may each extend between rotatable idler wheels 1221 mounted on a freely rotatable shaft and rotatable drive wheels 1223. Drive wheels 1223 may be mounted for rotation with and to a common drive shaft 1225 of a servo motor 1219 that may be interconnected via and in communication with a servo drive to the PLC 132 of the case former 1100. Conveyor belts 1213 may each have an upper belt portion that together may support one or more stacks of blanks 1211 thereon. PLC 132 may give an instruction (such as by order fulfilment processor 1300) to form a case, and if required, PLC 132 may cause upper belt portion of belt 214 to move towards in-feed conveyor 1204 by operation of servo motor 1219 rotating drive wheels 1223. In this way belt 214 can, if necessary, move a stack of blanks 1211 to a position adjacent to the in-feed conveyor 1204.

[0216] Positioned proximate the end of each magazine conveyor 1203 adjacent in-feed conveyor 1204 may be a vertically and longitudinally oriented plate 1230. Each plate 1230 may be supported by a plurality of plate support members 1235 that may be part of frame 1215. A lower longitudinally extending edge 1233 of plate 1230 may be positioned so that only the bottom blank in a stack of blanks (i.e. the blank that is immediately above the upper portions of the belts) can pass through a slot provided beneath lower edge 1233 of plate 1230 and the horizontal plane formed by the upper surface of the upper portions of the belts 1213. In this way, a slot 1231 can be provided that can permit a single blank at a time from the bottom of the stack to be pushed transversely through the slot and onto the in-feed conveyor 1204.

[0217] A pushing mechanism may be provided to respond to signals from PLC 132 of the case former to push a blank in a magazine from the bottom of the stack through the slot 1204 and onto in-feed conveyor 1204. The pushing mechanism may be any suitable type of device and may for example include a plurality of lugs 1217 located in the spaces between belts 1213. The lugs may be driven in a cyclical path by a common type crank mechanism (not shown) that may include a common pneumatic or hydraulic cylinder with a piston controlled by PLC 132 by activating appropriate valves to suitably control the flow of pressurized air/hydraulic fluid to the cylinder. The cylinder may have a piston arm attached to a longitudinally oriented bar member that may be mounted for rotation. The crank mechanism may be configured to provide a path for the lugs 1217 that commences in a position behind the bottom blank in a stack; then moves transversely between the belts 1213 while engaging the rear side edge of the bottom blank thereby pushing the bottom blank through the slot 1231. Once the crank mechanism reaches the end of the stroke, the lugs 1271 will descend downwards beneath the stack of blanks

and move transversely in an opposite direction back to the starting position, while at the same time not engaging the next bottom blank on the stack and passing beneath the stack. The path returns the lugs 1217 back to the start position so that when signalled by PLC 132 to load another blank onto conveyor 1204, the operation can be repeated.

[0218] In summary, PLC 132 can thus control motor 1219 and thus the movement of each conveyor 1203 as well as the movement of the lugs 1281, and thus is able to selectively move and transfer a single blank at a time onto in-feed conveyor 1204 from any one of magazines M1 to M16

[0219] Therefore, unlike in system 100 where a stack of case blanks may be fed to the alignment conveyor 206 by in-feed conveyor 204, in system 1000 separate individual case blanks may be fed in series and longitudinally by in-feed conveyor 1204 to alignment conveyor 1206. The particular sequence/order of case blanks that are placed onto in-feed conveyor 1204 of each case former 1100A-C may be determined and selected by PLC 132 such that case blanks may arrive at alignment conveyor 1206 in such a desired manner in which it is desired to process the blanks at least within case former 1100.

[0220] Further, each PLC 132 may maintain in its memory records of case blanks that have been placed onto in-feed conveyor 1204, to be formed and labelled. Each record may include information received by PLC 132 from order fulfilment processor 1300 (e.g., by way of the Fulfilment Order data structure) for a particular case blank to be formed and labelled. For example, this information may include the type/size/configuration of the case blank and the label information to be applied to the case blank. A new record can be added each time a request for a new case is received from order fulfilment processor 1300 and optionally records can be removed once a case has been formed and labelled. Thus, such records may be organized and maintained in sequence in the memory of PLC 132 using a conventional shift registering technique. In this way, the record for the next case blank scheduled to arrive at alignment conveyor 1206 may be provided at the output of the shift registers as that case blank arrives, and the type/configuration/size of that case blank and the label information for that case blank may be determined from the provided output.

[0221] Once transferred from in-feed conveyor 1204 to alignment conveyor 1206, the alignment conveyor 1206 may then under the control of PLC 132 move each blank sequentially to the pick up location. The pick up location may in part be determined by the front edge of each blank abutting the surfaces of a pair of spaced vertical plates 1218 (FIG. 57) as they are moved longitudinally downstream by alignment conveyor 1206.

[0222] Conveyor 1204 may be constructed substantially like conveyor 204 may include a pair of spaced conveyor belt 214 that may be driven by a suitable motor such as a DC motor or a variable frequency drive motor. The motor may be DC motor and may be controlled through a DC motor drive (such as are all sold by Oriental under model AXH-5100-KC-30) by PLC 132.

[0223] Conveyor belts 214 may have an upper belt portion supported on rollers (not shown). PLC 132 can as required cause upper portions of belts 214 to move longitudinally downstream towards alignment conveyor 1206. In this way belts 214 can move a series of spaced apart case blanks longitudinally downstream. PLC 132 can control the motor driving conveyor 1204 through the motor drive and thus

conveyor **1204** can be operated to move and transfer a series of blanks obtained from multiple magazine of magazines **M1** to **M16** towards and for transfer to the alignment conveyor **1206**.

[0224] Blank alignment conveyor **1206**, like alignment conveyor **206**, may also include a series of transversely oriented rollers **1208** that may be mounted for free rotating movement to a lower portion of the magazine frame **202**. A conveyor belt **1216** may be driven by a motor that and have a corresponding motor drive. This motor and motor drive for conveyor **1206** may also be controlled by PLC **132**. Belt **1216** may be provided with an upper belt portion supported on rollers **1208** and upon which one or more case blanks may be supported. Conveyor belt **1216** may be operated to move each case blank in turn further longitudinally until the front face of the blank abuts with a generally planar, vertically and transversely oriented inward facing surface of upstanding spaced plates **1218** so that each case blank is in turn placed into the pick up position.

[0225] Conveyor belt **1214** of conveyor **1204** and conveyor belt **1216** of conveyor **1206** may be made from any suitable material such as for example Ropanyl.

[0226] A sensor (not shown) such as an electronic eye model 42KL-D1LB-F4 made by ALLEN BRADLEY, may be located within the horizontal gap between belt **1214** and belt **1216**. The sensor may be positioned and operable to detect the presence of the front edge of a blank as each blank in turn begins to move over the gap between conveyor belt **1214** and conveyor belt **1216**. Upon detecting the front edge, sensor may send a digital signal to PLC **132** signalling that a particular blank (the size/configuration/type of which PLC **132** is aware) has moved to a position where conveyor **1206** can start to move. PLC **132** can then cause the motor for conveyor **1206** to be activated such that the top portion of belt **1216** starts to move the blank downstream. In this way, there can be a “hand-off” of each blank from in-feed conveyor **1204** to alignment conveyor **1206**.

[0227] Once the rear edge of each blank passes the sensor, a signal may be sent to PLC **132** which can then respond by sending a signal to shut down the motor driving belt **1214** of conveyor **1204**. Conveyor **1204** is then in a condition to await a further signal thereafter to feed the next blank in the series of blanks on the conveyor **1204** to alignment conveyor **1206**. Meanwhile alignment conveyor **1206** can be operated to move the blank placed thereon to the pick up location.

[0228] The presence of a blank on alignment conveyor **1206** at the pick up location may be detected by another sensor that may be the same type of sensor as sensors **240** and **242**. The sensor may detect the presence of the front edge of a blank at the pick up position and may send a digital signal to PLC **132** signalling that a blank is at the pick up position. At the pick up position, the blank may also be centred longitudinally by a pair of moveable longitudinally oriented side wall guides **1201** and **1202**.

[0229] Each blank may be suitably longitudinally and transversely positioned and oriented in a pick up position for proper engagement by both a labelling device and by one of the erector heads like erector heads **120a**, **120b** of system **100**. Side guide walls **1201** and **1202** may be mounted on tracks to a lower portion of a lower frame and both may be oriented generally vertically and may extend longitudinally for substantially the full length of alignment conveyor **1206**. The side guide walls **1201**, **1202** may be mounted in a similar manner as side walls **200**, **201** in system **100**.

[0230] A drive mechanism may be provided to drive each of side walls **1201** and **1202** on respective tracks. For side walls **1201** and **1202**, one or more drive mechanisms that are in electronic communication with PLC **132** can be provided. By way of example, a servo motor with gear head may be provided and be in electronic communication with PLC **132** through a servo drive. Examples that could be used are servo motor MPL-B1530U-VJ42AA made by ALLEN BRADLEY, in combination with servo drive 2094-BC01-MP5-S also made by ALLEN BRADLEY and gear head AE050-010 FOR MPL-A1520 made by Apex.

[0231] Like in carton forming system **100**, in case former **1100** lead screw rods may be inter-connected to servo motor/gear heads. Lead screw rods may pass through nuts, which may be fixedly secured to plates. Plates may be interconnected to spaced, generally vertically oriented bar members. Bar members may be interconnected to support frame (not shown) forming part of side walls. By activating servo motor/gear heads, the rotation of the servo may rotate the screw rods. As rods passes through nuts, the nuts can be moved laterally either inwards or outwards, thereby causing walls **1201**, **1202** to slide on tracks inwards or outwards depending upon the direction of rotation of screw rods. Encoders may be provided within or in association with servo drive motors and the encoders may rotate in relation to the rotation of the respective drive shaft of the servo drives. The encoders may be in communication with, and provide signals to the servo drives which can then pass on the information to PLC **132**. Thus, PLC **132** may be able to determine the longitudinal position of the screw rods in real time and thus the transverse position of side walls **1201**, **1202** and can operate the servo drives to adjust the position of the side walls **1201**, **1202**. The particular type of encoder that may be used is known as an “absolute” encoder. Thus once the encoders are calibrated so that a position of each the screw rod is “zeroed”, then even if power is lost to system **1000**, the encoders can maintain their zero position calibrations. With the transverse alignment mechanism of side guides walls **1201**, **1202** in abutment with the left and right side edges of the blank, guide walls can ensure he proper positioning of the datum line when the blanks are flattened is properly transversely aligned to be labelled by labelling device **1281** (only shown in FIG. **57**) and to be picked up by erector heads **120** of system **1100** and moved through folding and sealing apparatus **130**, as described above to achieve proper folding and sealing of the carton/case blank.

[0232] Optionally, PLC **132** may verify that the type/size/configuration of the case blank at the pick up location matches the expected case blank. For example, the top surface of each case blank may include a bar code identifying its type/size/configuration, and this bar code may be read at the pick up location by a suitably positioned bar code reader. The type/size/configuration of the case blank read from this bar code may be compared to the expected type/size/configuration of case blank, which may be determined from a record of the next scheduled case blank stored in memory of the PLC, as described above. Verification is successful when there is a match. When there is not a match, PLC **132** may issue a signal requesting manual operator intervention.

[0233] As indicated above, each case blank in each magazine may be generally initially formed and provided in a flattened tubular configuration such as by way of example is shown in FIGS. **10A-10E**. Each case blank has a height

dimension “H”; a length dimension “L”; and a major panel length “Q” (see FIG. 10B). The PLC of each case former 1100 may maintain in its memory each of these three dimensions for a case blank to be processed by case former 1100, and using these stored dimensions, the PLC can determine the necessary positions and/or movements of at least some of the components forming system 100, including the path of movement of erector heads 120a, 120b as the erector heads move and cycle through their processing sequences.

[0234] In this regard, for each case blank in each of magazines MI to M16, PLC 132 may have the information necessary to adequately process each case blank selected.

[0235] As was indicated above in relation to a representative case blank as shown in FIG. 11, each case blank in each magazine may be designated with a first datum line “W1” that passes through the mid-point of the fold line between panel D and flap K, and the mid-point of the fold line between panel B and flap J. This datum line W1 may be determined by PLC for blank to be processed, based on the dimensions H, L and Q of the blanks stored by the PLC or obtained by the PLC. Blank 111 may also be designated with a second datum line “W2” that may be determined by PLC 132 and which passes along and is generally parallel to the fold line between panel D and flap K, and the mid-point of the fold line between panel A and flap F. Datum W1 will be parallel to Datum W2. PLC 132 may also determine the relative position of the bottom of the erected case for the cases in each magazine as this will be aligned with a vertical datum plane passing through Datum W1 and Datum W2. Aligning the position datum W2 and of the datum plane with other components in case former 1100 will ensure that the case is properly positioned during processing. Also, the vertical distance R between datum W1 and the datum line W2 may be calculated by PLC. This can ensure that PLC knows where it needs to position the erector head so that top panel A, and accordingly, datum W1 are properly positioned throughout the processing of the blank by case former 1100.

[0236] Case former 1100 is able to track and modify the position of each case blank as it is being processed, and in particular the vertical position of the datum line W1 of the case blank as the case blank moves longitudinally through case former 1100 and as various components of case former 1100 engage the case blank during its movements. This will ensure that the case blank being processed is appropriately positioned relative to the system components so that the system components engage the case blank at the correct position on the blank during processing of the blank. For blanks that may be configured differently than blank 111, suitable adjustments may possibly be required to the dimensions and datums maintained by PLC 132 in order for carton former 1100 to be able to process a particular size/configuration/type of blank.

[0237] Labelling device 1281 may be mounted to the frame of carton/case former 1100 in the vicinity of alignment conveyor 1206. For example (although not depicted as such in the FIG. 57 for simplicity) labelling device 1281 may be mounted to a frame portion of carton former 1100 generally above where a case blank is located when the case blank is in the pick up location. Labelling device 1281 may be operable to print and apply one or more labels to one or more panels, preferably upward facing panels, of a blank located at the pick up location. Labelling device 1281 may be any suitable device such as the PLS-500 label application

system made by Paragon Labeling Systems Inc. (White Bear Lake, MN, USA) in conjunction with an integral print engine, such as a Lt408 print engine or a S84 Series print engine (e.g., model nos. S8408, S8412, or S8424) made by SATO America, Inc. (Charlotte, NC, USA). While in some embodiments a labelling device may apply a physically separate label to the case or case blank, in other embodiments the labelling device may apply printing to the case or case blank without providing the printing on a physically separate label.

[0238] As noted above, the label or labels applied to an upward facing panel(s) of each blank by labelling device 1281 may be specifically configured for that particular blank and may contain various types of information relating to an order of products to be fulfilled for the case to be formed from that particular blank. The label or labels may contain information providing certain order information including types of products to be loaded into the case to be formed from that blank, optionally including product codes of those products, the customer to whom the case is to be shipped and the customer’s address, as well as a case packing diagram that may be used by a product picker or filler in packing the case in a desired configuration with the products, and the locations in the warehouse building of the products. The label or labels may also contain a unique case identifier. Some or all of the information may be provided in bar code format, which a bar code reading device handled by an OFP may use to access the information from the label(s) once applied to the case blank.

[0239] The label is thus preferably printed and applied to the case blank while it is in a flattened configuration at the pick up location and prior to being erected and bottom sealed. This may make the label application process more reliable and provides the case with a unique identification.

[0240] Examples of the format of labels 1283a, 1283b that might be applied by labelling device 1281 are illustrated in FIGS. 59 and 60 respectively.

[0241] Once the label has been applied by labelling device 1281, case former 1100 may then proceed to erect and seal the case from the case blank in a manner like system 100 described above. It will be appreciated that PLC 132 may be in communication with the labelling device 1281 and can provide instructions for the printing and application of a suitable label or label(s) for the particular blank that is at the pick up location.

[0242] Once the case has been formed and sealed to form an erected case that is partially sealed and may be in a configuration such as shown in FIG. 16, the case may then be delivered from the discharge conveyor 117 (see for example FIG. 8) and be placed onto an accumulation conveyor that may be part of the respective case loader such as case loader 1400A, 1400B or 1400C associated with the particular carton former 1100A-C which formed the case.

[0243] The OFP may initiate the order picking process by picking an empty case from an accumulation conveyor and place the case onto an OFP cart 1413 (FIG. 62B) that can be moved around the warehouse where the products handled by system 1100 are located. Multiple cases may be picked and placed onto the OFP cart at the same time. The OFP will scan the appropriate bar code label on each case. This provides the OFP with all of the information necessary to pick and pack the order as predetermined by order fulfilment processor 1300. In some instances, some of all of this information may be retrieved by the OFP from the PLC 132 of the case

former or from order fulfilment processor **1300** using a unique case identifier encoded in the bar code label.

[0244] With all of the order information available to the OFP the OFP picks and packs the order of products directly into the case. The OFP may verify that the correct products are being packed into the case by bar code reading both the product and the case during the picking and packing operation, e.g., by comparing the UPC/ISBN provided by the bar code on the label(s) applied to the case with the UPC/ISBN on the product being packed.

[0245] Once the order (or part order for a particular case) has been completed by the OFP, such that all products for that case are loaded into the case, the case is directed to a final case sealing apparatus **1500A-C**. For example the OFP may place the loaded case with all products loaded therein onto a predetermined Random Top Case Seal (RTCS) in-feed conveyor that may feed the case to a suitable top sealing device. The RTCS may be adapted to read a label on the case placed by labelling device **1281** or otherwise located on the case, and as a result of information provided by the bar code the RTCS may automatically adjust the sealing components of the device so that it may close and seal the top of the case. The finished case may then be conveyed into the central case distribution system for further sorting and processing. An example of the type of suitable RTSC apparatus that could be employed as part of system **1000** is the random case sealer made by Marq Packaging Systems.

[0246] In operation of system **1000**, each one of a plurality of customers may use a customer order device such as devices **1200A**, **1200B** and **1200C**, including possibly accessing call center **1250**. Through operation of appropriate software on the order placement devices **1200A-C**, the order placement devices **1200A-C** may communicate directly or indirectly with order placement processor **1300** to so that multiple orders may be placed by customers, each orders being for one or more products, into order fulfilment processor **1300**.

[0247] Order fulfilment processor **1300** may process the customer orders received directly or indirectly from customer order devices **1200A-C**. Order fulfilment processor **1300** may for each order utilize its database that includes information that may be stored therein including information relating to: (a) details of all products that may be ordered by a customer through system **1000** including the actual physical dimensions of each product (such as the dimensions of the item package in which an item is packaged), optionally the weight of each product, and further optionally product codes associated with each product; (b) details of each of a plurality of types/sizes/configurations of cases/case blanks that can be used in system **1000** to package one or more products ordered by a customer including the dimensions of each case/case blank; (c) details of each case former (e.g., case formers **1100A-C**), including the types of cases that each case former is capable of forming, and optionally when a case former includes multiple magazines, the type of case blank provided in each of those magazines and the corresponding type of case that can be formed from each type of case blank, and further optionally the quantity of case blanks provided in each of those magazines; (d) information about each customer including the name of the entity and shipping address to which an order fulfilled by system **1000** is to be shipped; and (e) information about where each product is located in a warehouse building housing products that may be ordered.

[0248] Order fulfilment processor **1300** may also for each order use the product packaging utility to identify a suitable case and possibly an optimum case (e.g. having particular type/size/configuration) from the packaging suite of a limited and predetermined number of types/sizes/configurations of cases. Thus, when each order for specific products is input into order fulfilment processor **1300**, the product packaging utility can determine the optimal case or cases that can be used to package the products for each order (e.g. determine the least number of cases and/or the smallest size of cases that are required to package all the products in the customer order).

[0249] Order fulfilment processor **1300** may then for each order, generate a Fulfilment Order data structure that may be communicated by a communication link to the PLC of one of the case formers **1100A**, **1100B** or **1100C**. The order fulfilment processor **1300** may have determined to which of the case formers to send each Fulfilment Order data structure either randomly, or based on availability and/or suitability to handle the case type/size/configuration determined for a particular customer order. The Fulfilment Order data structure may include information including (i) the type/size/configuration of case determined by the product packaging utility that is required to be formed and labelled by the case former **1100A**, **1100B**, **1100C**; (ii) the particular magazine of the case former containing case blanks for forming the required type/size/configuration of case; (iii) a list of the particular product(s) from the customer order being fulfilled that are required to be loaded into the required case once formed, optionally arranged in the order in which the products should be loaded into the case once formed; (iv) optionally a diagram illustrating a desired optimal physical arrangement of the product(s) in loading the case; (v) optionally the location in the warehouse building of each particular product from the customer order being fulfilled; and (vi) customer shipping information for that case indicating the destination name and address for that case.

[0250] Each Fulfilment Order data structure may then be received and processed by the PLC **132** of the case former to which the data structure is sent. In particular, the PLC of the case former processes the Fulfilment Order data structure to identify the type/size/configuration of case (or cases) required, the particular magazine of the case former containing case blanks for forming each required type/size/configuration of case, and the contents of the label (or labels) to be applied. Once a required type/size/configuration of case and the particular magazine containing case blanks for forming the required type/size/configuration of case have been identified, the PLC of the case former causes a case blank from the identified magazine to be formed and labelled, generally as outlined above.

[0251] In particular, the PLC activates the appropriate conveyor of magazine conveyors **1203(1)** to **1203(16)**, corresponding to the identified magazine, if required to move a stack of case blanks of the identified type adjacent to in-feed conveyor **1204**. The transfer apparatus may, under the control of PLC **132**, then transfer the desired case blank from the identified magazine to the in-feed conveyor **1204**. The in-feed conveyor **1204** will then under the control of PLC **132** move that case blank longitudinally and then when signalled by PLC **132** to do so, transfer it to the alignment conveyor **1206**.

[0252] Alignment conveyor **1206** also under the control of PLC **132** may then move the case blank to the pick up

location and PLC 132 may then also cause the side walls 1201, 1202, to transversely align the case blank so that it is at the correct pick up position. PLC 132 may then cause labelling device 1281 to apply one or more labels like labels 1283a, 1283b to one or more upward facing surfaces of the panels of the case blank. PLC 132 may then cause the carton forming components of the carton former including an erecting head 120, to be moved by the movement subsystem to pick up the case blank from the pick up position and erect and partially seal the case from the case blank. PLC 132 may on an ongoing basis, as each case blank is being processed, cause any adjustments in components of folding and sealing apparatus 130 to be made to accommodate each case blank at they are processed.

[0253] Once the case has been formed and labelled for a particular customer product order, it may then be physically transferred to a respective case loader generally designated 1400A, 1400B or 1400C. The formed and labelled case can be picked up by the OFP in a warehouse building filled with the products. The OFP can scan and derive information from the label or labels applied to the case to identify the particular products that are to be loaded into that case and the OFP may then proceed to locate the products in the warehouse and fill the case with those products, possibly in the order listed by the scanning device. A packaging arrangement diagram either illustrated on the label on the case, or optionally displayed on a device such as the label scanner, if available, may be used by the OFP to load the case in the desired optimal manner.

[0254] Once the order (or part order for a particular case) has been completed by the OFP, such that all products for that case are loaded into the case, the case is directed to a final case sealing apparatus 1500A-C. The OFP may place the loaded case with all products loaded therein onto a predetermined Random Top Case Seal (RTCS) in-feed conveyor that may feed the case to a suitable top sealing device. The RTCS may read a label on the case placed by labelling device 1281 or otherwise located on the case, and as a result of information provided by the bar code the RTCS may automatically adjust the sealing components of the device so that it may close and seal the top of the case. The finished case may then be conveyed into the central case distribution system for further sorting and processing.

[0255] Various modifications are also possible in some embodiments. By way of example only, instead of providing for magazine conveyors 1203(1) to 1203(N) for magazines M1 to M(N), it may be possible to provide for a robotic system which could extract case blanks as demanded by PLC 132 from any one of a stack of case blanks in each of the magazines. The robotic system could either place a particular case blank that may be required on an in-feed conveyor. In other embodiments, the in-feed conveyor could be eliminated and the robotic system may place each case blanks that is required at the pick up position.

[0256] Of course, the above described embodiments are intended to be illustrative only and in no way limiting. The described embodiments of carrying out the invention are susceptible to many modifications of form, arrangement of parts, details and order of operation. The invention, rather, is intended to encompass all such modification within its scope, as defined by the claims.

[0257] When introducing elements of the present invention or the embodiments thereof, the articles “a,” “an,” “the,” and “said” are intended to mean that there are one or

more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements.

1. A method of fulfilling an order, said order comprising at least one product, said method comprising:

receiving an order comprising at least one product;
determining a suitable case from a plurality of available cases for holding said at least one product, said determining being a function of one or more characteristics of each said product of said at least one product and one or more characteristics of said plurality of available cases;
forwarding information identifying the suitable case to a case former;
providing a case blank corresponding to said suitable case to said case former;
erecting a suitable case from said case blank corresponding to said suitable case with said case former; and
prior to loading said suitable case with said at least one product, labelling said suitable case.

2. A method as claimed in claim 1 further comprising: after receiving said order:

accessing a memory providing information relating to said one or more characteristics of each product of said at least one product;
accessing a memory providing information relating to said one or more characteristics of each of said plurality of available cases;
and wherein said determining said suitable case derived from said information relating to said one or more characteristics of each product of said at least one product and said information relating to said one or more characteristics of each of said plurality of available cases.

3. A method as claimed in any one of claim 1 or 2, wherein said one or more characteristics of each product comprises the size of each product.

4. A method as claimed in any one of claims 1 to 3, wherein said characteristics of said plurality of available cases includes the size of each of said plurality of available cases.

5. A method as claimed in any one of claims 1 to 4, wherein said method comprises accessing a memory providing dimensions of each product of said at least one product.

6. A method as claimed in any one of claims 1 to 5, wherein said method comprises accessing a memory providing dimensions of each of said plurality of available cases.

7. A method as claimed in any one of claims 1 to 6, wherein said determining a suitable case for holding said at least one product is determined as a function of dimensions of each said product and dimensions of available cases.

8. A method as claimed in any one of claims 1 to 7, wherein said determining said suitable case comprises determining an optimal case size.

9. A method as claimed in claim 8, wherein said optimal case size is determined by a computing device operating a product packaging utility configured to determine an optimal case.

10. A method as claimed in any one of claims 1 to 9, wherein said case blank for said suitable case is provided to said case former from one of a plurality of magazines, and

wherein each of said plurality of magazines comprises case blanks corresponding to a different case size of said plurality of available case sizes.

11. A method as claimed in any one of claims **1** to **10**, further comprising forwarding information to a labelling device and wherein said case blank is labelled by said labelling device prior to erecting said suitable case from said case blank.

12. A method as claimed in any one of claims **1** to **11**, wherein at least one physically separate label is applied with said labelling device and wherein said at least one label contains information providing a list of each product to be loaded into said suitable case.

13. A method as claimed in any one of claims **1** to **11**, wherein said labelling provides: (i) information providing a shipping destination; and (ii) information relating to a list of each product to be loaded into said suitable case.

14. A method as claimed in claim **13**, wherein said labelling provides information relating to product codes associated with said each product.

15. A method as claimed in any one of claims **13** to **14**, wherein said labelling contains information relating to the location of each product on said list of products in a product storage facility.

16. A method as claimed in claim **15**, wherein said (i) information providing a shipping destination and (ii) information relating to a list of each product to be loaded into said suitable case can be obtained from said at least one label using a label scanner.

17. A method as claimed in claim **16**, wherein said shipping destination and said list of each product to be loaded into said suitable case are stored in a memory remote from said label scanner, and wherein said memory is accessed using said label scanner.

18. A method as claimed in any one of claims **1** to **17**, wherein said at least one product comprises a plurality of products and said method further comprises generating a case packaging spatial arrangement for said plurality of products in said suitable case based on dimensions of the suitable case and dimensions of each product of the plurality of products to be loaded into said suitable case.

19. A method as claimed in any one of claims **1** to **18** further comprising after erecting and labelling said suitable case, loading said suitable case with each said at least one product.

20. A method as claimed in claim **19**, wherein said loading comprises delivering said erected and labelled suitable case to a picker, and said picker thereafter loads said suitable case with each said at least one product.

21. A method as claimed in claim **20** further comprising generating a case packaging diagram based on dimensions of the suitable case and the dimensions of each product to be loaded into said suitable case and delivering said case packaging diagram to said picker and wherein said picker loads each said product using said case packaging diagram provided by said at least one label applied to said suitable case.

22. A method as claimed in claim **21**, wherein said case packaging diagram is provided in an electronic format that is reviewed by said picker using a scanning device adapted to scan said at least one label and display said case packaging diagram.

23. A method as claimed in any one of claims **19** to **22** further comprising after loading said suitable case with each

said at least one product, completing the sealing of said suitable case with each said at least one product inside said suitable case.

24. A method as claimed in claim **23** further comprising after completing the sealing of said suitable case, shipping the suitable case to the shipping destination contained on said at least one label.

25. A method as claimed in any of claims **1** to **24**, wherein said case blank is a tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, where said plurality of panels comprise a first panel and a second panel interconnected to said first panel, said second panel being rotatable relative to said first panel, and wherein said erecting said suitable case from said case blank comprises:

- (a) orienting said case blank in a generally flat orientation with said first and second panels being generally parallel to each other;
- (b) engaging said first panel;
- (c) engaging said second panel and rotating a second panel of said blank from said first orientation to a second orientation that is generally orthogonal to said first panel to open said tubular blank.

26. A method as claimed in claim **25** further comprising after (b), (c) rotating a flap of said carton blank relative to said first and second portions to a third orientation.

27. A method as claimed in claim **26**, wherein said rotating a flap of said carton blank comprises moving said carton blank longitudinally while said first panel remains generally orthogonal to said second panel, said flap being rotated relative to said first and second panels by cooperation of said movement and engagement with a folding apparatus.

28. A method as claimed in any of claims **1** to **24**, wherein said case blank for said suitable case is a tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, where said plurality of panels comprise a first panel and a second panel interconnected to said first panel, said second panel being rotatable relative to said first panel, and wherein said erecting a suitable case from said case blank corresponding to said suitable case with said case former comprises using an opening apparatus, said opening apparatus comprising:

- (i) a first engagement device for engaging said first panel of said blank;
- (ii) a second engagement device for engaging said second panel of said blank;

wherein said second engagement device is located on a panel rotating apparatus operable to rotate said second panel of said second panel from a first orientation wherein said first panel is in an opposed face to face relation with said first panel, to a second orientation wherein second panel is oriented at an angle to said first panel, such that said generally flattened tubular blank may be reconfigured to an open position; said erecting of said suitable case comprises:

- (a) engaging said first panel with said first engagement device;
- (b) engaging said second panel with said second engagement device;
- (c) rotating said second panel with said rotating device from a first orientation wherein said second panel is in an opposed face to face relation with said first panel, to a second orientation wherein second panel is oriented at

an angle to said first panel, such that said generally flattened tubular blank is reconfigured to an open configuration.

29. A method as claimed in any one of claims **1** to **28**, wherein said labelling of said suitable case comprises labelling said case blank prior to or during the erection of said suitable case from said case blank by said case former.

30. A method as claimed in any one of claims **1** to **28**, wherein said labelling of said suitable case comprises labelling said case blank prior to the erection of said suitable case from said case blank by said case former.

31. A method as claimed in any one of claims **1** to **18**, wherein said steps are performed automatically.

32. A method of fulfilling an order, said order comprising a plurality of products, said method comprising:

receiving an order comprising a plurality of products;

determining a plurality of suitable cases from said plurality of available cases for holding the said plurality of products, said determining being a function of at least one characteristic of each said product of said plurality of products and of at least one characteristic of said plurality of available cases;

forwarding information identifying the plurality of suitable cases to at least one carton former;

providing case blanks corresponding to each of said plurality of suitable cases to said at least one case former;

said at least one carton former erecting said plurality of suitable cases from said case blanks corresponding to each of said plurality of suitable cases with said one or more case formers;

prior to loading each of said suitable cases formed from said case blanks with said one or more case formers, labelling each of said suitable cases.

33. A method as claimed in claim **32**, wherein said at least one characteristic of each product comprises dimensions of each product.

34. A method as claimed in any one of claim **32** or **33**, wherein said at least one characteristic of said plurality of available cases comprises dimensions of each of said plurality of available cases.

35. A method as claimed in any one of claims **32** to **34** further comprising accessing a memory providing information relating to said at least one characteristic of each product of said plurality of products; and accessing a memory providing information relating to said at least one characteristic of each of a plurality of available cases.

36. A method as claimed in any one of claims **32** to **35**, wherein said determining a suitable case for holding the said at least one product is determined as a function of dimensions of each said product and dimensions of said plurality of available cases.

37. A method as claimed in any one of claims **32** to **36**, wherein said determining said plurality of suitable cases comprises determining cases having optimal case sizes.

38. A method as claimed in claim **37**, wherein said optimal case sizes are determined using a computer operating a product packaging utility configured to determine said optimal case sizes.

39. A method as claimed in any one of claims **32** to **38**, wherein said case blanks for said suitable cases are provided in a plurality of magazines.

40. A method as claimed in any one of claims **32** to **39**, wherein said case blanks are each labelled with said at least one label prior to erecting said respective suitable cases from said case blanks.

41. A method as claimed in any one of claims **32** to **40**, wherein said labelling for each of said suitable cases provides: (i) information relating to a shipping destination for each said suitable case; and (ii) information relating to a list of each product to be loaded into each said suitable case.

42. A method as claimed in any one of claims **32** to **41**, wherein said labelling provides information relating to product codes associated with said each product to be loaded into each suitable case.

43. A method as claimed in any one of claims **32** to **42**, wherein said labelling provides information relating to the location in a product storage facility of each product to be loaded into each suitable case.

44. A method as claimed in claim **43**, wherein each said (i) information relating to a shipping destination; and (ii) information relating to a list of each product to be loaded into said suitable cases are accessed from each said at least one label using at least one label scanner.

45. A method as claimed in claim **44**, wherein said shipping destination and said list of each product to be loaded into said suitable cases are stored in a memory remote from said at least one label scanner, and wherein said memory is accessed using said at least one label scanner.

46. A method as claimed in any one of claims **32** to **45** further comprising after erecting and labelling each of said suitable cases, loading said suitable cases with products to be loaded into each of said suitable cases.

47. A method as claimed in claim **46**, wherein said erected and labelled suitable case is delivered to a picker, and said picker thereafter loads said suitable case with each said product to be loaded into each suitable case.

48. A method as claimed in claim **47** further comprising generating a case packaging arrangement based on dimensions of the suitable case and dimensions of each product to be loaded into each suitable case and wherein said picker loads each said product using said case packaging arrangement provided by said at least one label applied to each said suitable case.

49. A method as claimed in claim **48**, wherein said case packaging arrangement is provided as a diagram.

50. A method as claimed in claim **49**, wherein said diagram is provided in an electronic format that is reviewed by a picker using a scanning device adapted to scan said at least one label and display said case packaging diagram.

51. A method as claimed in any one of claims **46** to **50** further comprising after loading each said suitable case with each said at least one product, completing the sealing of each said suitable case to seal each suitable case.

52. A method as claimed in claim **51** further comprising after completing the sealing of each said suitable case, shipping the suitable case to the shipping destination contained on said at least one label.

53. A method as claimed in any one of claims **32** to **52**, wherein said labelling of said suitable case comprises labelling said case blank prior to or during the erection of said suitable case from said case blank by said case former.

54. A method as claimed in any one of claims **32** to **52**, wherein said labelling of said suitable case comprises labelling said case blank prior to the erection of said suitable case from said case blank by said case former.

55. A method as claimed in any one of claims **32** to **45**, wherein said steps are performed automatically.

56. A system for fulfilling an order, said order comprising at least one product, said at least one product having a product characteristic, said system comprising:

An order fulfilment processor;

A first case blank magazine and a second case blank magazine, said first and second case blank magazines each holding at least one case blank, with the at least one case blank in the first magazine and the second magazine each having a case blank characteristic;

A carton former operable to erect a case from a case blank held in either of said first and second case blank magazines;

A case blank feeding apparatus operable to selectively feed a case from each of said first case blank magazines to said case former;

A labelling device operable to label a case blank prior to loading said case with at least one product;

wherein said order fulfilment processor is operable to (a) receive an order comprising at least one product; (b) determine a suitable case for said at least one product from said at least one case in said first and second case blank magazines as a function of said product characteristic of each said at least one product and said case blank characteristic of each said at least one case blank in said first and second case blank magazines; and (c) forward information identifying the suitable case to a case former;

and wherein said case former is operable to: (i) receive said information identifying the suitable case from said order fulfilment processor; (ii) select and receive a case blank from said case blank feeding apparatus for said suitable case from one of said first and second magazines; and (iii) erect said suitable case from said case blank;

and wherein said labelling device is operable to label said case blank of said suitable case prior to or after said case former has erected said suitable case from said case blank.

57. A system as claimed in claim **56**, wherein said order fulfilment processor is operable to (a) receive an order comprising said at least one product; (b) locate in a memory dimensions of each product of said at least one product and locate in a memory dimensions of said case blanks in said first and second magazines; (c) determine a suitable case for holding said at least one product as a function of said dimensions of each said product of said at least one product; (d) forward information identifying the suitable case to a case former.

58. A system as claimed in any of claim **56** or **57**, wherein said case former is operable for forming a container from a plurality of tubular blanks, each tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, wherein said plurality of panels comprise a first panel, and a second panel interconnected to said first panel, said second panel being rotatable relative to said first panel, said case former comprises:

a first engagement device for engaging said first panel of each said blank;

a second engagement device for engaging said second panel of each said blank, said second engagement device being located on a panel rotating apparatus operable to rotate said second panel of each said blank from a first orientation wherein said first panel is generally parallel to said first panel, to a second orientation

wherein second panel is oriented at an angle to said first panel, such that said generally flattened tubular blank may be reconfigured from a generally flattened configuration to an open configuration.

59. A system as claimed in claim **58**, wherein said case former further comprises an erector device and wherein said first engagement member, said second engagement member and said panel rotating apparatus comprise part of said erector device.

60. A system as claimed in claim **59**, wherein said first engagement device comprises a first suction cup device.

61. A system as claimed in claim **60**, wherein said second engagement device comprises a second suction cup device.

62. A system as claimed in any of claims **58** to **61**, wherein said first engagement device comprises a plurality of suction cup devices.

63. A system as claimed in claim **62**, wherein said second engagement device comprises a plurality of suction cup devices.

64. A system as claimed in any one of claims **58** to **63**, wherein said angle is approximately 90 degrees.

65. A system as claimed in any one of claims **58** to **64** further comprising (a) a plurality of magazines storing blanks for different available cases and (b) a transfer apparatus operable to selectively transfer selected blanks to said carton former.

66. A system for fulfilling an order, said order comprising a plurality of products, said plurality of products each having a product characteristic, said system comprising:

An order fulfilment processor;

A plurality of case blank magazines each holding a plurality of available case blanks, with the plurality of available case blanks in each of said plurality of magazines having a case blank characteristic;

A carton former operable to erect a case from a case blank of each of said plurality of case blank magazines;

A case blank feeding apparatus operable to selectively feed a case blank from each of said plurality of case blank magazines to said case former;

A labelling device operable to label each of said cases prior to loading each case with at least one product;

wherein said order fulfilment processor is operable to (a) receive an order comprising a plurality of products; (b) determine at least one suitable case for holding said plurality of products as a function of said product characteristic of said plurality of products and said case blank characteristics of each of said case blank in said plurality of case blank magazines; and (c) forward information identifying a suitable case to a case former;

and wherein said case former is operable to: (i) receive said information identifying a suitable case from said order fulfilment processor; (ii) select and receive a case blank from said case blank feeding apparatus corresponding to said suitable case from one of said available case blanks in one of said plurality of case blank magazines; and (iii) erect said suitable case from said case blank;

and wherein said labelling device is operable to label said case blank of said suitable case prior to or after said case former has erected said suitable case from said case blank.

67. A system as claimed in claim **66**, wherein said order fulfilment processor is operable to (a) receive an order comprising said plurality of products; (b) locate in a memory dimensions of each product of said plurality of products and locate in a memory dimensions of said available case blanks

in said plurality of case magazines; (c) determine a suitable case for holding the plurality of products as a function of said dimensions of each said product of said plurality of products; (d) forward information identifying the suitable case to a case former.

68. A system as claimed in any of claim **66** or **67**, wherein said case former is operable for forming a container from a plurality of tubular blanks, each tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, wherein said plurality of panels comprise a first panel, and a second panel interconnected to said first panel, said second panel being rotatable relative to said first panel, said case former comprises:

- a first engagement device for engaging said first panel of each said blank;
- a second engagement device for engaging said second panel of each said blank, said second engagement device being located on a panel rotating apparatus operable to rotate said second panel of each said blank from a first orientation wherein said first panel is generally parallel to said first panel, to a second orientation wherein second panel is oriented at an angle to said first panel, such that said generally flattened tubular blank may be reconfigured from a generally flattened configuration to an open configuration.

69. A system as claimed in claim **68**, wherein said case former further comprises an erector device and wherein said first engagement member, said second engagement member and said panel rotating apparatus comprise part of said erector device.

70. A system as claimed in any one of claim **68** or **69**, wherein said first engagement device comprises a first suction cup device.

71. A system as claimed in claim **70**, wherein said second engagement device comprises a second suction cup device.

72. A system as claimed in any of claims **68** to **71**, wherein said first engagement device comprises a plurality of suction cup devices.

73. A system as claimed in claim **72**, wherein said second engagement device comprises a plurality of suction cup devices.

74. A system as claimed in any one of claims **68** to **73**, wherein said angle is approximately 90 degrees.

75. A system for forming a container from a tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, wherein said plurality of panels comprise a first panel, and a second panel interconnected to said first panel, said second panel being rotatable relative to said first panel, said system comprising:

- (a) a plurality of magazines, each of said plurality of magazines for storing a plurality of tubular blanks in a generally flat configuration;
- (b) a case blank transfer apparatus for transferring a case blank from a selected one of said plurality of magazines to an erector head;
- (c) an erector head operable to received a case blank at a pick up location from said case blank transfer apparatus and open said case blank;
- (d) a folding and sealing apparatus; and
- (e) a movement sub-system having at least one movement apparatus connected to said erector head for moving

said erector head along a cyclical path extending between said pick up location and said folding and sealing apparatus.

76. A system as claimed in claim **75** wherein said erector head comprises: (i) a first engagement device for engaging said first panel of said blank; and (ii) a second engagement device for engaging said second panel of said blank; said second engagement device being located on a panel rotating apparatus operable to rotate said second panel of said blank from a first orientation wherein said first panel is in a generally parallel relation to said second panel, to a second orientation wherein second panel is oriented at an angle to said first panel, such that said generally flattened tubular blank may be reconfigured from a generally flattened configuration to an open configuration, and wherein said movement apparatus is operable to move said erector head, while said erector head is engaged with said first and second panels of said blank, and said blank is in an open configuration, towards said folding and sealing apparatus, so that a flap of said carton blank can be rotated relative to said first and second panels and said first flap by co-operation of said movement of said erector head relative to a plough member of said folding and sealing apparatus.

77. A system a claimed in claim **75** or **76** wherein said erector head is operable to be moved by said movement apparatus: from a first position that is a pick location where said erector device is operable to receive said blank from said case blank transfer apparatus; to a second position where said erector head is operable to open said blank to said open configuration; to a third position, such that during said movement of said erector head from said second position to said third position, a folding apparatus is operable to fold said second to at least partially form a case bottom.

78. A system a claimed in claim **77** wherein said erector head is operable to be moved from said third position to a fourth position wherein said erector device is operable to disengage from said case.

79. A system as claimed in any one of claims **75** to **77** further comprising a controller operable to control the operation of said first engagement device, said second engagement device, said panel rotating apparatus and said movement apparatus.

80. A system as claimed in claim **79** wherein said controller is operable to control said case blank transfer apparatus.

81. A system as claimed in any one of claims **75** to **80** wherein at least some of said plurality of magazines contain different size, shape or configurations of case blanks.

82. A system as claimed in claim **80** wherein at least some of said plurality of magazines contain different size, shape or configurations of case blanks and wherein said controller is operable to store in a memory a record of the size, shape or configuration of case blanks held in said some of said plurality of magazines.

83. A system as claimed in any of claims **75** to **82** wherein said case blank transfer apparatus comprises an in-feed conveyor operable to receive selected case blanks from each of said plurality of magazines.

84. A system as claimed in any of claim **83** wherein said case blank transfer apparatus further comprises an alignment conveyor operable to receive selected case blanks from said in-feed conveyor.

85. A system as claimed in any of claim **83** or **84** wherein said case blank transfer apparatus further comprises a maga-

zine conveyor operable to deliver single case blanks from a stack of blanks to said in-feed conveyor.

86. A system as claimed in any one of claims **75** to **85** wherein said at least one movement apparatus comprises:

a vertical movement device, said vertical movement device adapted for connection to a first erector device;

a horizontal movement device connected to a frame, said horizontal movement device operable sliding longitudinal movement relative to said frame;

said vertical movement device being interconnected to said horizontal movement device for vertical sliding movement relative to said horizontal movement device;

a drive apparatus operable to drive said horizontal movement device horizontally and drive said vertical movement device vertically relative to said horizontal movement device

a controller to control said drive apparatus;

whereby through operation of said drive apparatus, said controller can cause said vertical movement device and said horizontal movement device to move said erector device along a path in space having vertical and longitudinal components.

87. A system as claimed in claim **86** wherein at least one movement apparatus comprises first and second movement apparatuses arranged in opposed relation to each other, said first movement apparatus for moving a first erector device along a path, and said second movement apparatus for moving a second erector device along said same path, said first erector head being out of phase with said second erector head along said path.

88. A system as claimed in any one of claims **75** to **86** wherein said at least one movement apparatus comprises:

a continuous belt;

a generally vertically oriented support member having a first pulley positioned proximate an upper end of said belt support member, said support member adapted for connection to a first erector device;

a slidable pulley block, said block being adapted for sliding longitudinal movement on a support member, and said block having a series of spaced pulleys, said vertical support member being interconnected to said pulley block for vertical sliding movement relative to said pulley block;

first and second longitudinally spaced belt drives, each of said belt drives being independently operable to rotate at varying speeds and in the same and opposite directions to each other, said belt drives both operable to drive said belt on opposed sides of said vertical support member;

a controller to control the speed and direction of rotation of said belt drives;

said vertical support member being received adjacent said block and being supported by said belt for vertical sliding movement relative to said block, said belt extending from a fixed location on said vertical support tube upwards to a first pulley on said block, longitudinally to said first belt drive, from said first belt drive over a second pulley of said block, upwards to said first pulley of said vertical member, downwards to a third pulley of said block to said second belt drive; from said second belt drive and longitudinally to over a fourth pulley of said slide block, and then downward to a second fixed location of said vertical member;

whereby through operation of said first and second belt drives, said controller can cause said vertically oriented support member and said first erector device connected thereto, to be moved up and down relative to said block and move longitudinally right and left with said block between said first and second belt drives with said block on said block support member such that said erector device follows a path in space having vertical and longitudinal components.

89. A system as claimed in any one of claims **75** to **88**, further comprising a flap rotating apparatus operable to rotate a flap of said blank relative to said first and second panels after said blank is in said open configuration.

90. A system as claimed in claim **89** wherein said flap rotating apparatus is located on said erector head.

91. A system as claimed in claim **90** wherein said flap rotating apparatus is a first flap rotating apparatus and comprises part of a folding and sealing apparatus.

92. A system as claimed in claim **91** wherein said folding and sealing apparatus comprises a second flap rotating apparatus operable to rotate a second flap of said blank relative to said first and second panels and said first flap when said blank is in said open configuration.

93. A system as claimed in claim **92** wherein said first and second flaps are minor bottom leading and trailing flaps.

94. A system as claimed in any one of claims **91** to **93** wherein said folding and sealing apparatus comprises a third flap rotating apparatus and a fourth flap rotating apparatus operable to rotate third and fourth flaps respectively of said blank relative to said first and second panels and said first and second flaps.

95. A system as claimed in claim **94** wherein said third and fourth folding and sealing apparatuses are operable to operate to rotate third and fourth flaps respectively of said blank relative to said first and second panels and said first and second flaps, after said first and second flaps have been rotated.

96. A system as claimed in claim **95** wherein said third and fourth flaps are major bottom flaps.

97. A system as claimed in claim **96** wherein said third flap rotating apparatus and said fourth flap rotating apparatus are operable to rotate third and fourth flaps respectively of said blank relative to said first and second panels and said first and second flaps, after said first and second flap rotating apparatuses have rotated said first and second flaps.

98. A system as claimed in claim **97** further comprising a sealing apparatus operable to seal said first, second, third and fourth flaps in a folded configuration to from a bottom of said container.

99. A system a claimed in any one of claims **75** to **98** further comprising a controller for controlling the operation of said panel rotating apparatus.

100. A system as claimed in any one of claims **75** to **99** wherein said first engagement device comprises a plurality of suction cup devices.

101. A system as claimed in claim **100** wherein said second engagement device comprises a plurality of suction cup devices.

102. A system a claimed in claim **100** or **101** further comprising a controller for controlling the operation of said panel rotating apparatus and a valve device in communication with said plurality of suction cup devices of said first and second engagement devices, said controller operable to

control said valve device to control the operation of said plurality of suction cup devices of said first and second engagement devices.

103. A system as claimed in claim **102** further comprising a plurality of vacuum generators in communication with each of said plurality of suction cups, and wherein said controller controls said valve device to control the flow of pressurized air from a source of pressurized air to said vacuum generators.

104. A system as claimed in any one of claims **75** to **103** further comprising a movement apparatus for moving said erector device along a path, said movement apparatus operable for moving said erector device from a position where said first rotating apparatus opens said blank, to a folding and sealing apparatus where a bottom of said open blank is closed.

105. A system as claimed in any one of claims **75** to **103** further comprising a movement apparatus for moving said erector device along a path, said movement apparatus operable for moving said erector device from a position where said first rotating apparatus opens said blank, to a folding and sealing apparatus where a bottom of said open blank is closed.

106. A system as claimed in any of claim **83** wherein said case blank transfer apparatus further comprises a guide wall apparatus proximate said alignment conveyor and operable to transversely align each said blank at a pick up location.

107. A system as claimed in claim **106** wherein said guide wall apparatus comprises first and second, spaced apart, generally parallel, longitudinally oriented side members the location of which is transversely adjustable.

108. A method for forming a container from a tubular blank comprising a plurality of panels and flaps interconnected to provide a generally flattened tubular configuration, wherein said plurality of panels comprise a first panel, and

a second panel interconnected to said first panel, said second panel being rotatable relative to said first panel, said method comprising:

- a. Obtaining a selected case blank from one magazine of a plurality of magazines, each of said plurality of magazines storing a stack of tubular blanks in a generally flat configuration;
- b. Transferring said selected case blank to an erector head;
- c. Erecting said selected case blank with said erector head; and
- d. folding and sealing said selected case blank.

109. A method as claimed in claim **108** wherein said erecting said selected case from said case blank comprises:

- i) orienting said case blank in a generally flat orientation with first and second panels being generally parallel to each other;
- ii) engaging said first panel with said erector head;
- iii) engaging said second panel with said erector head and rotating said second panel of said blank from said first orientation to a second orientation that is generally orthogonal to said first panel to open said tubular blank.

110. A method as claimed in claim **109** further comprising after (iii), (iv) rotating a flap of said carton blank relative to said first and second portions to a third orientation.

111. A method as claimed in claim **110**, wherein said rotating a flap of said blank comprises moving said blank longitudinally while said first panel remains generally orthogonal to said second panel, said flap being rotated relative to said first and second panels by co-operation of said movement and engagement with a folding apparatus.

112. A method as claimed in any one of claims **109** to **111** wherein at least some of said plurality of magazines contains blanks for different size, shape or configurations of cases.

* * * * *